

Main

Range of Product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Mounting and fixing accessories
Accessory / Separate Part Type	Fixing column
Offer type	Without mirror
Product Compatibility	XUSL.E...16 to XUSL.E...61 with 2 beams
Accessory / separate part destination	Safety light curtain type 4 Safety light curtain type 2

Complementary

Ambient Air Temperature for Operation	-22...131 °F (-30...55 °C) -22...131 °F (-30...55 °C)
Ambient Air Temperature for Storage	-22...158 °F (-30...70 °C) -22...158 °F (-30...70 °C)
Kit composition	1 x cable gland(s), Pg 11
Column height	39.37 in (1000 mm)
Height protected	24.02 in (610 mm)
Net Weight	8.16 lb(US) (3.7 kg)

Ordering and shipping details

Category	22455-LIGHT CURTAINS - XUSL
Discount Schedule	DS2
GTIN	3389119619196
Nbr. of units in pkg.	1
Package weight(Lbs)	11.68 lb(US) (5.3 kg)
Returnability	No
Country of origin	IT

Packing Units


Unit Type of Package 1	PCE
Package 1 Height	5.51 in (14 cm)
Package 1 width	7.87 in (20 cm)
Package 1 Length	42.91 in (109 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	11.68 lb(US) (5.3 kg)
Package 2 Height	5.51 in (14 cm)
Package 2 width	7.87 in (20 cm)
Package 2 Length	43.31 in (110 cm)

Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Dimensions

With XUSZFB2



With XUSZFB1



Mounting and Clearance

