SPECIALTY REELS



WOODHEAD® HEAVY-DUTY HAND-WIND REELS ARE DESIGNED WITH A ROBUST STEEL CONSTRUCTION FOR THE STORAGE OF EXTENSION CORDS, POWER CABLES, ROPES AND HOSES, PROVIDING PROTECTION FROM CRIMPING, KNOTS AND DAMAGE

Woodhead heavy-duty hand-wind reels for storage applications are perfect for storing extension cords, power cables, ropes, hoses or for continuous power service. Hand-wind reels provide easier, more organized cable storage versus wrapping cable, eliminating cable knots and kinks. The heavy-duty hand-wind reels, robust steel construction protects service cords from damage.

FEATURES AND BENEFITS

| Heavy-duty steel design | Provides longer-lasting and increased robustness | | |
|----------------------------|--|--|--|
| Large-spool design | Allows greater storage capacity | | |
| Steel-rod frame | Improves support | | |

APPLICATIONS

- Construction site
- Portable tools
- Service vehicle

B

Hand Wind Reels 100' 12/3 SOW to 200' 16/3 SOW



Features and Benefits

• Capable of storing 200' of 16/3, 125' of 14/3 or 100' of 12/3 SOW cord

• Heavy-duty design provides convenient storage of extension cords, power cables, rope or hose

Reference Information

UL File No.: E22769 (930 only) E19795 (reel with cable) CSA File No.: LR29921 (930 only)

(H) (H)

Electrical

Versions with cord: NEMA 5-15 plug and connector Cord: SOW, 600V rated

Physical

Construction: Steel with yellow powder coat finish, no spring hand wind design

Models with Cord: NEMA 5-15 plug at working end of cord and NEMA 5-15 connector at reel end

| S | |
|----|--|
| | |
| w. | |
| Ō | |
| | |

| Cord Type | Cord Length Woodhead No. | | Order No. | |
|-----------|--------------------------|---------|-------------|--|
| | | 930 | 130087-0057 | |
| 14/3 SOW | 15.24m (50.0') | 930B143 | 130087-0059 | |
| 14/3 SOW | 30.48m (100.0') | 930D143 | 130087-0064 | |
| 12/3 SOW | 15.24m (50.0') | 930B123 | 130087-0058 | |
| 12/3 SOW | 30.48m (100.0') | 930D123 | 130087-0063 | |

Features and Benefits

- NEMA 4 rating provides protection from water or dust, indoor and out
- Cable guide is adjustable every 5° over a 270 degree arc allowing for the exact configuration to suit the application
- Standard models cover the four most popular wire sizes
- Ratchet design prohibits annoying "lock-out" when cable is fully extended
- Containerized mainspring for safe, simple handling and replacement
- Reel includes cable (except ERA4000)

Electrical

Collector Ring Rating: 375A

Physical

Primary Cord Entry: 1" NPT

Construction: Cast Aluminum with yellow powder coat finish

Working End: Flying leads; ball stop not included Ratchet Lock: Easily disengaged as needed

Tension: Easily adjusted
Junction Box: Large, easy-access
Spring: Containerized, easily replaceable

Environmental

NEMA Rating: NEMA 4

| Wire Gauge | Length | Current Rating | Woodhead No. | Order No. |
|------------|----------------|----------------|--------------|-------------|
| less cable | | 375 | ERA4000 | 130083-0286 |
| 2 | 15.24m (50.0') | 250 | ERA4250 | 130083-0289 |
| 1 | 15.24m (50.0') | 250 | ERA4150 | 130083-0288 |
| 1/0 | 12.19m (40.0') | 350 | ERA4040 | 130083-0287 |
| 2/0 | 12.19m (40.0') | 375 | ERA4940 | 130083-0291 |

Hose Reels



Features and Benefits

- Steel construction and epoxy powder-coat finish for long life
- Containerized mainspring for safe, simple handling and replacement
- Adjustable guide arm with four-roller guide to suit the application
- Brass and Stainless Steel fluid path and nitrile seals minimize maintenance
- Ratchet lock and easy tension adjustment for ease of use
- Hose stop included on all models

Physical

Hose Type: EPDM/SBR tube, red SBR cover Maximum Hose Temperature: 176° F (80° C)

| Inlet Hose Fitting (NPT) | Hose Inner Diameter (in.) | Hose Length | Pressure (psi) | Woodhead No. | Order No. |
|--------------------------|---------------------------|----------------|----------------|--------------|-------------|
| 1/4 | 1/4 | 9.14m (30.0') | 300 | DA230 | 130161-0005 |
| 3/8 | 3/8 | without hose | 300 | DA300 | 130161-0006 |
| 3/8 | 3/8 | 9.14m (30.0') | 300 | DA330 | 130161-0007 |
| 3/8 | 3/8 | 15.24m (50.0') | 300 | DB350 | 130161-0009 |
| 1/2 | 1/2 | without hose | 300 | DB400 | 130161-0012 |
| 1/2 | 1/2 | 15.24m (50.0') | 300 | DB450 | 130161-0014 |