	GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS		
	www.globtek.com	Model No. Connector		
	186 Veterans Drive,			
	Northvale, NJ 07647			
	Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A	

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://en.globtek.com/terms-and-conditions/).

Prop 65 Statement:https://en.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.

A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS	
www.globtek.com	Model No. Connector	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A
Fax (201) 784-0111		

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
Α	Initial release	QA	08/16/2022	QA


3D CAD FILE:

https://www.globtek.com/file/dl/plug-usbc-241smt-th-4bc2ls.stp

AGENCY ONLINE DOCUMENTS


RoHS/RoHS3 Declaration	https://www.globtek.com/pdf/rohs_cert/01t3a000004Wn6DAAS		
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf https://www.globtek.com/pdf/conflict-minerals.pdf		
Conflict Minerals Declaration			
Prop 65 Statement	https://en.globtek.com/prop-65-statement.pdf		

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.





PIN DEFINITION			
PIN	Signal Name	PIN	Signal Name
A1	GND	B12	GND
A2	TX1+	B11	RX1+
A3	TX1-	B10	RX1-
A4	VBUS	B9	VBUS
A5	CC	B8	SBU2
A6	D+	B7	D-
A7	D-	B6	D+
A8	SBU1	B5	VCONN
A9	VBUS	B4	VBUS
A10	RX2-	B3	TX2-
A11	RX2+	B2	TX2+
A12	GND	B1	GND



LCP

GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS	
www.globtek.com	Model No. Connector	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A
Fax (201) 784-0111		

NOTES: 1.MATERIALI:

CONTACTS: Copper alloy T=0.15

INSULATOR: HIGH TEMPERATURE PLASTIC

UL 94V-0,

Shell: STEEL T=0.15

2.ELECTRICAL PERFORMANCE:

INSULATION RESISTANCE: 100Mohm MIN. CONTACT RESISTANCE: 40mohm MAX. DIELECTRIC WITHSTANDING: 100 VAC

CURRENT RATING: 5A MIN.
3.MECHANICAL PERFORMANCE:

MATING FORCE: 5~20N UNMATING FORCE: 8~20N DURABILITY: 10000 CYCLES


Temperature Life, Vibration, Cyclic Temperature and Humidity, Thermal Shock, Mixed Flowing Gas and etc.:

https://www.globtek.com/pdf/ENVIRONMENTAL.pdf

GlobTek, Inc. www.globtek.com	GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS		
	www.globtek.com	Model No. Connector		
	186 Veterans Drive,			
	Northvale, NJ 07647			
	Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A	

Packing:	

GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS	
www.globtek.com Model No. Connector		
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A
Fax (201) 784-0111		



	GlobTek, Inc.	Drawing Title: USB 2.0 5A 1 260°C Surface Mount 12 Male -55°C~+85°C Gold Copper Alloy Type-C SMD USB Connectors ROHS		
	www.globtek.com	Model No. Connector		
	186 Veterans Drive,			
	Northvale, NJ 07647			
Tel. (201) 784-1000	Part No./Ordering No. PLUG-USBC-241SMT-TH-4BC2LS	Rev A		
	Fax (201) 784-0111			

PACKAGING	
Packing Spec P/N:	
Box Qty:	7500
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	350 x 350 x 220
Master Carton Cubic Volume (r	m³): 0.03
Master GW (Kg):	6.8 kg
wt Ea. (Kg):	0.00 kg
wt Ea. (Kg):	0.00 kg
LABEL SPECS:,	
PACK SPEC:	