

# M12-M panel feed through 5pol.B-cod.IP67



Part number	21 03 341 1505
Specification	M12-M panel feed through 5pol.B-cod.IP67
HARTING eCatalogue	https://b2b.harting.com/21033411505

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	Circular connectors M12
Element	PCB adapter
Specification	Straight for rear mounting

#### Version

Termination method	Reflow soldering termination (THR)
Gender	Male
Shielding	Shielded
Number of contacts	5
Coding	B-coding
Locking type	Screw locking

### Technical characteristics

Rated current	4 A
Rated voltage	50 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Overvoltage category	III
Insulation resistance	>10 <sup>8</sup> Ω
Contact resistance	≤10 mΩ
Tightening torque	2 Nm Lock nut



#### Technical characteristics

Limiting temperature	-40 +85 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP67 mated condition
Isolation group	I (600 ≤ CTI)

#### Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Copper alloy
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

# Specifications and approvals

Specifications IEC 61076-2-101	pecifications
--------------------------------	---------------

#### Commercial data

Packaging size	10
Net weight	22.9 g
Country of origin	Romania
European customs tariff number	85366990

Product data sheet 21 03 341 1505 M12-M panel feed through 5pol.B-cod.IP67



## Commercial data

GTIN	5713140228122
eCl@ss	27460201 PCB connector (board connector)