# 5-102398-5 ACTIVE

#### **AMPMODU**

TE Internal #: 5-102398-5

Connector Assembly, Receptacle, Wire-to-Board, 14 Position, .1 in [2.54 mm] Centerline, Insulation Displacement (IDC), 2 Row, Black,

Wire & Cable

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings

Connector Product Type: Connector Assembly

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 14

Centerline (Pitch): 2.54 mm [ .1 in ]

### **Features**

#### **Product Type Features**

| Froduct Type realures                 |                    |
|---------------------------------------|--------------------|
| Applied Pressure                      | Standard           |
| Connector Product Type                | Connector Assembly |
| Connector & Housing Type              | Receptacle         |
| Connector System                      | Wire-to-Board      |
| Sealable                              | No                 |
| Connector & Contact Terminates To     | Wire & Cable       |
| Configuration Features                |                    |
| Number of Positions                   | 14                 |
| Number of Rows                        | 2                  |
| Electrical Characteristics            |                    |
| Termination Resistance                | 12 mΩ              |
| Insulation Resistance                 | 5000 ΜΩ            |
| Dielectric Withstanding Voltage (Max) | 750 V              |
| Body Features                         |                    |
| Primary Product Color                 | Black              |
| Contact Features                      |                    |
|                                       |                    |

Socket

Copper Alloy

Tin

3 A

Contact Type

Contact Base Material

Contact Current Rating (Max)

PCB Contact Termination Area Plating Material



### **Termination Features**

| Termination Method to Wire & Cable   | Insulation Displacement (IDC) |
|--------------------------------------|-------------------------------|
| Mechanical Attachment                |                               |
| Mating Retention                     | Without                       |
| Connector Mounting Type              | Cable Mount (Free-Hanging)    |
| Housing Features                     |                               |
| Housing Entry Configuration          | Both Ends Closed              |
| Housing Material                     | Thermoplastic                 |
| Centerline (Pitch)                   | 2.54 mm[.1 in]                |
| Dimensions                           |                               |
| Connector Length                     | 17.78 mm[.7 in]               |
| Connector Height                     | 6.1 mm[.24 in]                |
| Compatible Insulation Diameter Range | 1.27 mm[.05 in]               |
| Wire Size                            | .12 – .326 mm²                |
| Row-to-Row Spacing                   | 2.54 mm[.1 in]                |
| Usage Conditions                     |                               |
| Operating Temperature Range          | -65 – 105 °C[-85 – 221 °F]    |
| Operation/Application                |                               |
| Circuit Application                  | Signal                        |
| Industry Standards                   |                               |
| Glow Wire Rating                     | Standard Part - Not Glow Wire |
| Approved Standards                   | CSA LR7189, UL E28476         |
| UL Flammability Rating               | UL 94V-0                      |
| Packaging Features                   |                               |
| Packaging Quantity                   | 170                           |
| Packaging Method                     | Tray                          |
|                                      |                               |

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant                               |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant                               |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |



| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
|--|---|
| Halogen Content                        | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability              | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**

TE Part # 58074-1

MTA 50/100/156 MANUAL TOOL
FRAME

TE Part # 102540-5

14 AMPMODU MT COVER DR .100CL

## **Customers Also Bought**

TE Part #3-641213-4
PCB Header: Polyester, Vertical, 2.54
mm

TE Part #1-770973-0
14P MINI UMNL R/A HDR ASSY SN
A/L LOW PRO HDR 16P VERT HT
03P MINI UMNL HDR ASSY AU LF



TE Part #1-794067-0 14P MINI UMNL HDR W/DH SN

TE Part #350570-7
UMNL SOK 24-18 AUBR

TE Part #61291-1 RECPT .093 DIA 22-18 PTPPHBRZ TE Part #5104338-4 A/L LOW PRO HDR 20P VERT HT

### **Documents**

### **Product Drawings**

14 AMPMODU MT ASSY DR.100CL SN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-102398-5\_U.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-102398-5\_U.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-102398-5\_U.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

AMPMODU\_INTERCONNECTION\_SYSTEM\_SECTION5\_CONT

English

### **Product Specifications**

**Application Specification** 

English

### Product Environmental Compliance

**TE Material Declaration** 

English