

DIES ACCEPTABLE FOR USE IN 2280380-[] TOOL


USED ON

DWG NO 2280635
THIS DRAWING IS A CONTROLLED DOCUMENT.

PRODUCT FAMILY	CATALOG NUMBER	TE PRODUCT	RG/U CABLE WIRE SIZE	SDE DIE SET ONLY
		ULTRA-FAST FASTON (STRAIGHT) [.110/.125 in.] RECPT.	[26-14 AWG] 0.13-2.0 mm ²	58628-2
		ULTRA-FAST FASTON (STRAIGHT) [.187/.250 in.] RECPT. [.250 in.] TABS		
PIN AND SOCKET CONNECTORS	82068	D-SUBMINIATURE 20 DF PIN AND SOCKET CONTACTS (AMPLIMITE*)	[28-24 AWG] 0.08-0.2 mm ²	58448-3
		D-SUBMINIATURE 22 DF PIN AND SOCKET CONTACTS (AMPLIMITE*)	[24-20 AWG] 0.2-0.6 mm ²	
		TYPE II PIN AND SOCKET CONTACTS	[28-22 AWG] 0.08-0.3 mm ²	90800-2
		TYPE III+ AND TYPE VI PIN AND SOCKET CONTACTS	[24-14 AWG] 0.2-2.0 mm ²	58541-2
	82181	.093 SOFT SHELL COMMERCIAL PIN AND SOCKET CONTACTS	[28-24 AWG] 0.08-0.2 mm ²	58495-2
			[24-20 AWG] 0.2-0.6 mm ²	
		.062 SOFT SHELL COMMERCIAL PIN AND SOCKET CONTACTS	[18-16 AWG] 0.8-1.4 mm ²	90872-2
			[24-18 AWG] 0.2-0.9 mm ²	
		MR PIN AND SOCKET CONTACTS	[20-14 AWG] 0.6-2.0 mm ²	90871-2
			[30-24 AWG] 0.05-0.2 mm ²	90870-2
		UNIVERSAL MATE-N-LOK* II AND UNIVERSAL MATE-N-LOK PIN AND SOCKET CONTACTS	[24-18 AWG] 0.2-0.9 mm ²	90869-2
			[20-14 AWG] 0.6-2.0 mm ²	58514-2
			[.060-.130 in.] 1.52-3.30 mm Ins. Dia.	90548-2
			[20-14 AWG] 0.6-2.0 mm ²	90546-2
	MINI-UNIVERSAL MATE-N-LOK PIN AND SOCKET CONTACTS	[.130-.200 in.] 3.30-5.08 mm Ins. Dia.	90547-2	
		[26-22 AWG] 0.13-0.3 mm ²	90758-2	
		[22-18 AWG] 0.3-0.9 mm ² or Two [22 AWG]	90759-2	
	COMMERCIAL MATE-N-LOK PIN AND SOCKET CONTACTS	[20-16 AWG] 0.6-1.4 mm ² or Two [20 AWG]	90760-2	
[24-18 AWG] 0.2-0.9 mm ²		90574-2		
RECEPTACLE AND TAB CONNECTORS	---	DYNAMIC SERIES D-3 CONTACTS	[24-20 AWG] 0.2-0.56 mm ²	90683-2
		CTS-100 CONTACTS	[20-16 AWG] 0.5-1.42 mm ²	90684-2
	65481	AMPSEAL* AUTOMOTIVE RECEPTACLES	[26-22 AWG] 0.13-0.3 mm ²	58517-2
		AMP SUPERSEAL* 1.5 SERIES CONTACTS	0.5-1.5 mm ²	58529-2
				58583-2
TERMINALS AND SPLICES	65505	UNINSULATED TERMINALS AND SPLICES (SOLISTRAND)	[22-10 AWG] 0.3-5.0 mm ²	58545-1

1. THE FOLLOWING DIES CANNOT BE USED IN THIS TOOL BECAUSE THE CRIMP FORCE REQUIRED EXCEEDS THE LIMITS OF THE TOOL.
58423-1, 2063030-1, 91965-2, 58530-2, 58525-2, 58630-2, 58524-2, 217212-2.

2280635-[] MICRO SDE DATA SHEET

DWN C. KERSTETTER 26MAY2015		MATERIAL -		HEAT TREAT -	
CHK R. DOBSON 26MAY2015		 TE Connectivity			
APVD R. DOBSON 26MAY2015					
NAME MICRO SDE DATA SHEET					
SCALE 1:1		SIZE A2		DRAWING NO 2280635	
SHEET 1		OF 1		REV B1	

DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
0 PLC	± -	1 PLC	± -
2 PLC	± -	3 PLC	± -
4 PLC	± -		
ANGLES ±		-	
SURFACE TEXTURE		√	

B1	REVISED	04/2017	AW	RD
P	LTR	REVISION RECORD	DATE	DWN
			APVD	

LOC	-
DIST	-

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES (TE). IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TE PERSONNEL, WITHOUT AUTHORIZATION FROM TE (www.te.com).