



- 1. FOR USE WITH, INTERCOMP RG-11/U TYPE CABLE, .068 DIA CENTER CONDUCTOR, .285 DIA DIELECTRIC, .385 O.D. JACKET, USE STRIP LENGTH A.
- 2. FOR USE WITH, BELDEN 8213 CABLE & THE COAX PORTION OF BELDEN 9232 CABLE, USE STRIP LENGTH B.
- 3. USE CRIMPING TOOL: 220015-1.
- 4. SEE I.S. 1914-1
- 5. RG-9/U, RG-9A/U, RG-9B/U, RG-214/U, RG-8/U, RG-8A/U & RG-213/U.
- 6. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER DRENAUD/D/SINISI

VIEW A  
RECOMMENDED STRIP LENGTH  
SCALE 2:1  
VIEW B

OBSOLETE	RG-11/U	B	9-51713-0	225526-4	225887-2	225886-8		
SUPERSEDED BY 5225886-7	TIMES FM-8	B	9-51713-0	225526-6	225887-2	225886-7		
6	OBSOLETE	A OR B, SEE CABLE	9-51713-0	225596-4	225887-2	225886-6		
OBSOLETE	ALPHA 9847	B	51713-2	225596-4	225887-3	225886-5		
SUPERSEDED BY 5225886-4	RG-11/U	B	9-51713-2	225526-4	9-225887-0	225886-4		
OBSOLETE	RG-9/U,9A/U,9B/U & 214/U	B	51713-2	225596-2	9-225887-0	225886-2		
SUPERSEDED BY 5225886-1		B	9-51713-4	225596-2	9-225887-0	225886-1		
FOR USE WITH CABLE:	VIEW	3	FERRULE QTY=1	2	CONTACT QTY=1	1	PLUG ASSY QTY=1	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DATE	9-18-90	BY	J. LIPPERT
CHK	11-7-91	BY	J. LIPPERT

OTHER PARTS CHECKED:

APPROVAL	DATE
PHILLIPS	11-7-91

PRODUCT SPEC: 108-12020

APPLICATION SPEC

SIZE: A2

CODE: 00779

QTY: 225886

SCALE: 4:1

SHEET: 1 of 1

REV: KS

REVISONS		DATE	BY
F	DIR		
K/S	REVISED PER ECO-17-011152	15NOV2017	LN
			RS

225886