3030324

https://www.phoenixcontact.com/us/products/3030324



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Commercial data

| Item number | 3030324 |
|--------------------------------------|---------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Sales key | BE29 |
| Product key | BE2Z2X |
| Catalog page | Page 178 (C-1-2019) |
| GTIN | 4055626029184 |
| Weight per piece (including packing) | 2.68 g |
| Weight per piece (excluding packing) | 2.635 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

3030324

https://www.phoenixcontact.com/us/products/3030324



Technical data

Product properties

| Product type | Jumper | | |
|--|--|--|--|
| Number of positions | 2 | | |
| Pitch | 8.2 mm | | |
| Electrical properties | | | |
| Maximum load current | 41 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) | | |
| Connection data | | | |
| Maximum load current | 41 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) | | |
| Dimensions | | | |
| Width | 14.7 mm | | |
| Height | 20.38 mm | | |
| Depth | 20.38 mm | | |
| Pitch | 8.2 mm | | |
| Material specifications | | | |
| Color | red | | |
| Material | Copper | | |
| Flammability rating according to UL 94 | V0 | | |
| | | | |


Mounting

Insulating material

PA

3030324 https://www.phoenixcontact.com/us/products/3030324

Drawings



Schematic diagram



3030324

https://www.phoenixcontact.com/us/products/3030324



Classifications

ECLASS

| ECLASS-11.0 | 27141140 |
|-------------|----------|
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

ETIM

| | ETIM 8.0 | EC000489 | | |
|--------|-------------|----------|--|--|
| UNSPSC | | | | |
| | UNSPSC 21.0 | 39121400 | | |

3030324 https://www.phoenixcontact.com/us/products/3030324



Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com