


**INDUSTRIAL PARTS
PACKAGE: INDIVIDUAL PE BAG.**

NOTE FOR PLUG:
MATERIAL: HOUSING-POLYCARBONATE, CLEAR.
TERMINAL-0.36[.014] THICK PHOSPHOR BRONZE.
THICK GOLD IN LOCALIZED GOLD PLATE.
AREA, GOLD FLASH OVER THE REMAINDER.
OVER 2.54um[.000100] THICK NICKEL UNDERPLATE.




| P1 | | P2 |
|----|--------|----|
| 1 | BLACK | 1 |
| 2 | RED | 2 |
| 3 | GREEN | 3 |
| 4 | YELLOW | 4 |


SEC: A-A

| NO | ITEM | DESCRIPTION | Q'TY |
|----|-----------|-------------|------|
| ① | CABLE | | 1PCS |
| ② | PLUG | 4P4C 50U" | 2PCS |
| ③ | CABLE TIE | | 1PCS |
| ④ | | | |
| ⑤ | | | |
| ⑥ | | | |

| PART NO | DRAWING NO | WIRE LENTH "L" | BUYER COLOR | VENDOR COLOR | CUT LENGTH |
|----------------------|------------|------------------|-------------|--------------|-------------|
| 512-26-4400-SV-0005F | A | 1525±20 (5FT) | Silver | S49-1 LIGHT | 1525-1535MM |
| 512-26-4400-SV-0007F | B | 2135±30 (7FT) | Silver | S49-1 LIGHT | 2135-2145MM |
| 512-26-4400-SV-0010F | C | 3050±60 (10FT) | Silver | S49-1 LIGHT | 3050-3060MM |
| 512-26-4400-SV-0012F | D | 3660±60 (12FT) | Silver | S49-1 LIGHT | 3660-3670MM |
| 512-26-4400-SV-0014F | E | 4270±60 (14FT) | Silver | S49-1 LIGHT | 4270-4280MM |
| 512-26-4400-SV-0025F | F | 7625±100 (25FT) | Silver | S49-1 LIGHT | 7625-7635MM |
| 512-26-4400-SV-0050F | G | 15250±150 (50FT) | Silver | S49-1 LIGHT | 15250-15260 |



A, B, C, D. Folding



E, F, G. Folding

| REVISED | VERSION | BASIS | CONTENTS |
|----------|---------|--------|-------------|
| 12-02-20 | A/0 | T0210A | NEW DRAWING |
| | | | |
| | | | |

| CnC Tech, LLC Industrial Cable and Connector Technology | |
|--|----------------------|
| IDRAWING NO: 671-319 | CUSTOMER: L-671 |
| ITEM NO: 4C LINE CORD P+P PLUG | UNIT: mm |
| DATE: 2012-02-20 | ISSUE (A/0) |
| DRAWN: _____ | QA: _____ |
| SALES DEPT: _____ | SALES MANAGER: _____ |