2134078-1 - ACTIVE

TE Internal #: 2134078-1 PCB Spring Contact, Preloaded - C-Clip, Side Protected, Uncompressed Height 1.2 mm [.047 in], Length 2.4 mm [.094 in], Width 1.05 mm [.041 in]

View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > PCB Spring Contacts

Spring Finger Type: Preloaded - C-Clip

Scalable: No

Side Protected: Yes

Uncompressed Height: 1.2 mm [.047 in]

Product Length: 2.4 mm [.094 in]

Features

Product Type Features

Spring Finger Type	Preloaded - C-Clip
Scalable	No
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Side Protected

Yes

1

Number of Positions

Contact Features

Contact Underplating Material	Nickel				
PCB Contact Termination Area Plating Material	Gold				
Contact Base Material	Copper Alloy				
Contact Working Range (Low)	.7 mm[.028 in]				
Contact Working Range (High)	1 mm[.039 in]				
Point of Contact Area Plating Material	Gold				
Contact Current Rating (Max)	1.5 A				
Dimensions					
Uncompressed Height	1.2 mm[.047 in]				
Product Length	2.4 mm[.094 in]				
Product Width	1.05 mm[.041 in]				
Usage Conditions					

C For support call+1 800 522 6752

08/13/2023 11:44PM | Page 1

2134078-1

PCB Spring Contact, Preloaded - C-Clip, Side Protected, Uncompressed Height 1.2 mm [.047 in], Length 2.4 mm [.094 in], Width 1.05 mm [.041 in]



Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	8000
Packaging Method	Tape & Reel
EU RoHS Directive 2011/65/EU	Compliant
For compliance documentation, visit the product page on TE.com>	
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts


2134078-1

PCB Spring Contact, Preloaded - C-Clip, Side Protected, Uncompressed Height 1.2 mm [.047 in], Length 2.4 mm [.094 in], Width 1.05 mm [.041 in]



TE Part # 1447360-8 SHIELD FINGER 1312 A TYPE	TE Part # 1513430-1 PCB ANTENNA SINGLE BAND TAPE AND REELED	TE Part # 2305018-2 USB TYPE C, REC IPX8 ON BOARD DUAL SMT	TE Part # 2199001-1 SHIELD FINGER 1210 EMBOSS PACKING

Customers Also Bought



IShield Finger, Loose Piece	STNDOL	SPRING FINGER 1.2H	SPRING FINGER 1.45H	
TE Part #2199001-1 SHIELD FINGER 1210 EMBOSS PACKING				
Documents				

Product Drawings SHILED FINGER 1210 EMBOSS PACKING

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2134078-1_B.2d_dxf.zip

2134078-1

PCB Spring Contact, Preloaded - C-Clip, Side Protected, Uncompressed Height 1.2 mm [.047 in], Length 2.4 mm [.094 in], Width 1.05 mm [.041 in]



English

Customer View Model ENG_CVM_CVM_2134078-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2134078-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Environmental Compliance MD_2134078-1_06172016312_dmtec

English

MD_2134078-1_06172016312_dmtec

English