# 9080GF6

Terminal block, Linergy, sectional fuse holder, natural colored block, 30A, 600 V



Main		
Range of Product	9080G	
Product Type	Terminal block	
Localisation on Device	Fusible	
Color	Natural	
Quantity	Set of 10	

Complementary

- Compression y	
Voltage Rating	600 V AC/DC
Current Rating	30 A UL 30 A CSA
Wire Size	AWG 18AWG 10 copper
Mounting Type	35 mm DIN rail 9080GH track
Certifications	CSA file 62144 class 6228 01 CE UL recognized E60616 CCN XCFR2
Protection Type	Fingersafe DIN 57470
Electrical Connection	Pressure wire clamp
Material	Nylon block Tin plated copper busbar
Ambient Air Temperature for Operation	-40221 °F (-40105 °C)
Electrical Connrection Tightening Torque	Clamp terminal zinc plated steel 1820 lbf.in (2.032.26 N.m) : AWG 18AWG 10 copper)
Height	2.33 in (59.18 mm)
Width	2.19 in (55.63 mm)
Depth	0.75 in (19.05 mm)
Density	16 per foot
Compatible End Barrier	GF6B

#### Ordering and shipping details

Category	21702-9080 G (NOT GCB)	
Discount Schedule	CP5	
GTIN	785901155034	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.80 oz (22.7 g)	
Returnability	Yes	
Country of origin	MX	

# Packing Units

Unit Type of Package 1	PCE
Onit Type of Fackage T	I OL
Package 1 Height	2.20 in (5.6 cm)
Package 1 width	0.79 in (2 cm)
Package 1 Length	2.20 in (5.6 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

#### Contractual warranty

Warranty	18 months