


In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C(NOTES 3)	
OPERATING HUMIDITY RANGE	20% TO 80%(NOTES 2)	STORAGE HUMIDITY RANGE	40% TO 70%(NOTES 2)(NOTES 3)	
VOLTAGE		APPLICABLE CONNECTOR	DF81※:30S-0.4H(##)	
CURRENT		APPLICABLE CABLE		
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
<p>REMARKS</p> <p>NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT</p> <p>NOTE2: NON CONDENSING</p> <p>NOTE3: THE TERM "STORAGE" REFERS TO PRODUCTS STORED FOR A LONG PERIOD PRIOR TO MOUNTING AND USE. THE OPERATING TEMPERATURE AND HUMIDITY RANGE COVERS THE NON-CONDUCTING CONDITION OF CONNECTORS AFTER BOARD MOUNTING AND THE TEMPORARY STORAGE CONDITIONS OF TRANSPORTATION, etc</p> <p>Unless otherwise specified, refer to JIS C 5402,IEC60512.</p>				
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				
		APPROVED	MH. YAMANE	13. 11. 06
		CHECKED	MH. TSUCHIDA	13. 11. 05
		DESIGNED	AH. MIYAZAKI	13. 11. 01
		DRAWN	AH. MIYAZAKI	13. 11. 01
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-340821-02	
		SPECIFICATION SHEET	PART NO.	DF81-30P-LCH(52)
		HIROSE ELECTRIC CO., LTD.	CODE NO.	CL662-8107-3-52
				△ 1/1