

MAG-MATE

TE Internal #: 2232237-1

Magnet Wire Terminals, Tab, Mating Tab Width .25 in [6.35 mm], 21

– 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, MAG-

MATE

View on TE.com >



Terminals & Splices > Magnet Wire Terminals











Magnet Wire Terminal Type: Tab

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Aluminum Wire Size: .41 – .65 mm

Features

Product Type Features

Compatible With Discrete Wire Type Magnet Wire, Solid Contact Features Magnet Wire Terminal Type Tab Mating Tab Width 6.35 mm[.25 in] Mating Tab Thickness .81 mm[.032 in] Terminal Plating Material Tin Terminal Orientation Straight Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions Terminal Height 21.2 mm[.835 in]		
Magnet Wire Terminal Type Mating Tab Width 6.35 mm[.25 in] Mating Tab Thickness .81 mm[.032 in] Terminal Plating Material Tin Terminal Orientation Straight Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions	Compatible With Discrete Wire Type	Magnet Wire, Solid
Mating Tab Width 6.35 mm[.25 in] Mating Tab Thickness .81 mm[.032 in] Terminal Plating Material Tin Terminal Orientation Straight Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions	Contact Features	
Mating Tab Thickness .81 mm[.032 in] Terminal Plating Material Tin Terminal Orientation Straight Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions	Magnet Wire Terminal Type	Tab
Terminal Plating Material Tin Terminal Orientation Straight Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions	Mating Tab Width	6.35 mm[.25 in]
Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Hole Dimensions	Mating Tab Thickness	.81 mm[.032 in]
Termination Features Termination Method to Wire & Cable Insulation Displacement (IDC) Mechanical Attachment Mating Retention Type Hole Dimensions	Terminal Plating Material	Tin
Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Hole Dimensions	Terminal Orientation	Straight
Mechanical Attachment Mating Retention Type Hole Dimensions	Termination Features	
Mating Retention Type Hole Dimensions	Termination Method to Wire & Cable	Insulation Displacement (IDC)
Dimensions	Mechanical Attachment	
	Mating Retention Type	Hole
Terminal Height 21.2 mm[.835 in]	Dimensions	
	Terminal Height	21.2 mm[.835 in]

.41 – .65 mm

Aluminum Wire Size



Magnet Wire Size	.32 – .51 mm
Stock Thickness (Magnet Wire Side)	.79 mm
Product Length	21.21 mm[.835 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 150 °C[-85 – 302 °F]
Operation/Application	
Compatible With Wire Base Material	Aluminum, Copper
Packaging Features	

Reel/Carton

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 1217031-1 MAG-MATE 250FTAB 22-20 016TPBR



TE Part # 1217924-1 TAB,250 FASTON,MAG-MATE



TE Part # 1742398-1 TAB, FASTON, 250 SERIES, MAG-MATE


















Also in the Series | MAG-MATE







Magnet Wire Terminals(435)



Customers Also Bought



TE Part #63570-1 MAG-MATE 048 PIN 23-27 TPBR



TE Part #1-659304-0 SHEAR BLADE, UPPER





TE Part #3-659663-5
TUBE INSERTION, SINGLE

TE Part #548657-8
BLADE TRIM, DUAL

TE Part #6-659667-7
BLADE TRIM, SINGLE

TE Part #7-659667-2
BLADE TRIM, DUAL

TE Part #7-659667-2
BLADE TRIM, SINGLE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2232237-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2232237-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2232237-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Magnet Wire Terminals & Splices

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Magnet Wire Terminals, Tab, Mating Tab Width .25 in [6.35 mm], 21 – 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, MAG-MATE

