



Metric table

Dimensions in: millimeters - inches

1 d ₁	2 d ₂ Thread	3 Length l					d ₃	h ₁	h ₂
		15	20	25	30	40			
45 1.77	M 6	15 .59	20 .79	25 .98	30 1.18	40 1.57	18 .71	27 1.06	16 .63
45 1.77	M 8	15 .59	20 .79	30 1.18	40 1.57	-	18 .71	27 1.06	16 .63
45 1.77	M 10	20 .79	30 1.18	-	-	-	18 .71	27 1.06	16 .63
55 2.17	M 6	20 .79	25 .98	40 1.57	-	-	20 .79	33 1.30	19 .75
55 2.17	M 8	20 .79	30 1.18	40 1.57	-	-	20 .79	33 1.30	19 .75
55 2.17	M 10	15 .59	20 .79	30 1.18	-	-	20 .79	33 1.30	19 .75

Specification

- Three-lobed knob
Nylon plastic
 - Temperature resistant up to 230 °F (110 °C)
 - Black, matte finish
- Threaded stud
Steel
 - Zinc plated
 - Molded-in
- RoHS compliant

Information

V3-B-P three-lobed knobs have an aesthetically pleasing shape, provide a comfortable grip and expand the range of clamping options.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- Three-Lobed Knobs V3-B (with Brass Blind Tapped Insert)
- Three-Lobed Knobs V3-B-FP (with Brass Through Tapped Insert)

On request

- Stainless steel insert

How to order 1 2 3 V3-B-P-45-M10-30	1	Handle diameter d ₁
	2	Thread d ₂
	3	Length l