



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switch. 3-Pole 3-Wire Non-Fused in a type 4/4X 316 grade Stainless Steel enclosure. Rated 600VAC (200A). Special features: viewing window.

|  |   |
|--|---|
| mechanical service life (switching cycles) typical | 8000  |
| fastening method                                   | SURFACE   |
| number of poles                                    | 3   |
| suitability for operation                          | DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS |
| <b>Electricity</b>                                 |   |
| ampacity   | 200 A   |
| supply voltage frequency rated value 50/60 Hz      | Yes   |
| <b>Model</b>                                       |   |
| product brand name                                 | SIEMENS   |
| product type designation                           | HEAVY DUTY SWITCH                               |
| special product feature                            | VIEWING WINDOW                                  |
| type of electrical connection                      | MECHANICAL LUGS                                 |
| <b>Mechanical Design</b>                           |   |
| design of the housing                              | TYPE 4X   |
| design of the actuating element                    | SINGLE THROW                                    |
| material   | 316 STAINLESS STEEL                             |
| <b>General product approval</b>                    |   |
| certificate of suitability                         | UL98  |

last modified:

9/16/2021 

