

Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 1250x750x420mm, IP65, IK10

NSYPLA1274G

Main

| | |
|---------------------------|--|
| Range | Thalassa |
| Product name | Thalassa PLA |
| Enclosure type | Multi-purpose |
| Product or component type | Suitable enclosure |
| Version | PLA |
| Nominal height | 1250 mm |
| Nominal width | 750 mm |
| Nominal depth | 420 mm |
| Enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 1 rear panel 1 door |

Complementary

| | |
|-----------------------------|--|
| Body type | Sealed top and bottom part assembled with side parts |
| Door type | Plain front |
| Number of doors | 1 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 4 points lock, 5 mm double-bar |
| Accessibility for operation | Rear Front |
| Removable parts | Door by hinges Rear panel by fixing element |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |
| Standards | UL 508 A IEC 62208 |
| NEMA degree of protection | NEMA 3R NEMA 3 NEMA 3S NEMA 1 NEMA 13 NEMA 2 NEMA 12 NEMA 5 |

NEMA 3X

| | |
|-------------------------------|--|
| Product certifications | DNV Marine Veritas UL/cUL listed |
|-------------------------------|--|

| | |
|------------------------------------|----------|
| Electrical insulation class | Class II |
|------------------------------------|----------|

Environment

| | |
|--------------------------------|--|
| IP degree of protection | IP65 conforming to IEC 60529 (completely sealed) |
|--------------------------------|--|

| | |
|--------------------------------|---|
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) |
|--------------------------------|---|

| | |
|------------------------|--------------------------------|
| Fire resistance | 960 °C conforming to IEC 62208 |
|------------------------|--------------------------------|

| | |
|--|-------------|
| Ambient air temperature for storage | -35...90 °C |
|--|-------------|

Packing Units

| | |
|-------------------------------|-----|
| Unit Type of Package 1 | PCE |
|-------------------------------|-----|

| | |
|-------------------------------------|---|
| Number of Units in Package 1 | 1 |
|-------------------------------------|---|

| | |
|-------------------------|----------|
| Package 1 Height | 126.0 cm |
|-------------------------|----------|

| | |
|------------------------|---------|
| Package 1 Width | 78.0 cm |
|------------------------|---------|

| | |
|-------------------------|---------|
| Package 1 Length | 48.0 cm |
|-------------------------|---------|

| | |
|-------------------------|---------|
| Package 1 Weight | 38.0 kg |
|-------------------------|---------|

Offer Sustainability

| | |
|---------------------------------|-----------------------|
| Sustainable offer status | Green Premium product |
|---------------------------------|-----------------------|

| | |
|-------------------------|-----------------------------------|
| REACH Regulation | REACH Declaration |
|-------------------------|-----------------------------------|

| | |
|--------------------------|---|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
|--------------------------|---|

| | |
|---------------------|-----|
| Mercury free | Yes |
|---------------------|-----|

| | |
|------------------------------|---|
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
|------------------------------|---|

| | |
|-----------------------------------|---------------------|
| RoHS exemption information | Yes |
|-----------------------------------|---------------------|

| | |
|---------------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
|---------------------------------|---|

Recommended replacement(s)