48 INCHES LENGTH






Connector A 132259 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-316DB Continuity/Hi-Pot Connector B 252147 MCX Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



| Part #: Description: | RG-316DS | Part #: | 252147 |
|-------------------------|---|--|---|
| Description: | DO 040DD 070400 | | |
| | RG-316DB - ST 0.102 | Description: | MCX BHD JK RG316 DB 500 |
| Dielectric: | ST | Type: | MCX |
| Shielding: | Double Braid | Gender: | Jack |
| Diameter: | 0.102 | Body Type: | Straight |
| Impedance: | 50 Ohm | Contact Type: | Solder |
| Sheathing: | None | Polarity: | Standard |
| Testing: | Continuity Hi-Pot | Impedance: | 50 Ohm |
| Length: | 48 Inches | Mounting: | Bulkhead - Rear Mount |
| | | Body Material: | Brass |
| | | Body Finish: | Gold |
| | | IP Rating: | None |
| | | Contact Material: | Beryllium Copper |
| | | Contact Finish: | Gold |
| | | Max. Freq.: | 6 GHz |
| | | Booting: | MCX Jack Straight BHD |
| | | Clocking: | 0° |
| | Shielding: Diameter: Impedance: Sheathing: Testing: | Shielding: Double Braid Diameter: 0.102 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot | Shielding: Double Braid Gender: Diameter: 0.102 Impedance: 50 Ohm Contact Type: Sheathing: None Testing: Continuity Hi-Pot Length: 48 Inches Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: |

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/MCX-ST-JK G316D 48I

Part No

Q-2Q012000R048I

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-2Q012000R048I

Manufacturer: Amphenol Custom Cable

Description: SMA-RA-JK/MCX-ST-JK G316D 48I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

