The Cowboy 5G

Ceiling Mount Dome Antenna





BT151007

The ideal ceiling mount antenna for transmitting & receiving in 360-degree view

- Built for the USA band ranges covering 617 MHz to 6000 MHz
- Wideband omnidirectional indoor antenna for use with signal boosting systems
- Low return loss and stable performance in a compact, lightweight design
- Up to +5 dBi gain, designed for 50 Ohm Systems
- Easy to install




ELECTRICAL STUFF			Product Specifications may change without prior notice.				
Item No.		BT151007					
Frequency Range		MHz	617-698	698-960	1710-2700	3400-4000	4900-6000
Gain		dBi	1.8±0.5	2.0±0.5	3.0±1.0	4.0±1.0	4.5±1.0
VSWR			≤1.8	≤1.8	≤1.5	≤1.7	≤1.7
Polarization			Vertical				
Beam Width	Horizontal	deg	360				
	Vertical		90	80	35	30	28
PIM, 3rd Order, 2 x 20 W		dBc	≤-153				
Input Power, maximum		watt	50				
Impedance		ohm	50				

ļ	RADIATION PATTERNS
	HORIZONTAL
	900 MHz
	1710 MHz

TION RNS

MECHANICAL STUFF						
Connector Type		N-Female				
Size	mm, in	225 x 150, 8.86 x 5.90				
Packing Size	mm, in	210 x 210 x 110, 8.25 x 8.25 x 4.33				
Antenna Weight	kg, lb	45, 0.99				
Operational Temperature	°C, °F	-40 to 55, -40 to 131				
Radome Material and Color		ABS, White, RAL 9003				
Cable Length	cm, in	34, 13.38				
Coax Type		RG141				



2500 MHz

VERTICAL









