



FEATURES:

- Meets requirements of MIL-P-55149/1A.

MATERIALS:

Binding Post Body, Nuts, Lockwasher: Gold Plated Brass
 Insulation: Nylon MIL-P-20693
 Flat Washer: Brass
 Insulator: Nylon
 Hex Nut: Steel

RATINGS:

Voltage: Hand-held testing: 30VAC/60VDC Max.
 Hands free testing in controlled voltage environments: 1500 VRMS
 Operating Temperature: +80°C (+176°F) Max.
 Current: 30 Amperes

ORDERING INFORMATION: Model 5018-
 *=Color, -0 Black, -2 Red, -4 Yellow, -5 Green, -6 Blue, -9 White
 Ordering Example: 5018-2 Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies. Made in USA

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA