

Electrostatic Discharge (ESD) Port Kits and Wrist Strap

- Accommodate standard ESD wrist strap 4mm plug
- Wrist strap provides rapid and continuous drain of electrostatic charge between a person and the surface that the wrist strap is bonded to, thus preventing damaging static discharge into equipment

- Can be mounted to front or back of rack or cabinet for convenient access

- Bent 45°, acts as a hook to hold wrist strap
- Two-hole configuration provides anti-rotation and prevents loss of bond
- Barrel permanently marked with the protective earth (ground) symbol
- Engineered to comply with US and International grounding requirements

**RGESD2-1****RGESD2B-1****RGESDWS**

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
ESD Port Kit for #12-24 or M6 Rail Fasteners			
RGESD2-1	Two-hole ESD port with 5/8" hole spacing; provided with an ESD protection sticker, .16 oz. (5cc) of antioxidant, and two each #12-24 x 1/2" and M6 x 12mm thread-forming screws.	1	20
ESD Port Kit for Cage Nut Rail Fasteners			
RGESD2B-1	Two-hole ESD port with 5/8" hole spacing; provided with an ESD protection sticker, .16 oz. (5cc) of antioxidant, two cage nut bonding studs and two #12-24 bonding nuts.	1	20
ESD Wrist Strap			
RGESDWS	Adjustable fabric ESD wrist strap with 6' coil cord, banana plug, 1 megohm resistor and 4mm snap.	1	—

ESD port must be attached to a grounded member.
ESD wrist strap sold separately.