


D-SUBMINIATURE CONNECTORS:
K86X Series
 High Density Vertical PCB Mount and Solder Cup

K86X Series Dimensions
 Dimensions in mm



Number of Contacts (Shell Size)	Dimensions (Inch/mm)					
	A	A1	B	C	D	E
15 (E)	.643	.666	.984	1.213	.090	.010
	16.33	16.92	24.99	30.81	2.29	0.25
26 (A)	.971	.994	1.312	1.541	.090	.020
	24.66	25.25	33.32	39.14	2.29	0.51
44 (B)	1.511	1.534	1.852	2.088	.090	.020
	38.38	38.96	47.04	53.04	2.29	0.51
62 (C)	2.159	2.182	2.500	2.729	.094	.023
	54.84	55.42	63.50	69.32	2.41	0.58

A = Exterior of Female Shell (S)
 A1 = Interior of Male Shell (P)

Generated Part Number

K86X-EA-15P

Part Number Builder

K86X	-	E	A	15	P		
Series		Shell Type	Pin Type	Contact Option	Contact Type	Mounting Option	Plating Option

Series

K86X - D-Subminiature Vertical Connector

Contact Shell Size

- 15 Contacts
- 26 Contacts
- 44 Contacts
- 62 Contacts

Contact Construction, Pin Type

- A - Precision Formed, Solder Cup (Not Available with BR/BRJ)
- D - Precision Formed, Vertical Pin (PCB Mount)

Contact Type

- P - Pin Contact (Plug)
- S - Socket Contact (Receptacle)

Mounting Option

- Blank - Through Hole
- BR - #4-40 Threaded Boardlocks
- BRJ - #4-40 Threaded Boardlocks and #4-40 Jackscrews Installed
- K - #4-40 Threaded Bushings
- KJ - #4-40 Bushings and #4-40 Jackscrews

Plating Option

- Blank - Gold Flash
- 30 - 30µ" Gold

Contact Kycon for Other Options