

Front adapters - FLKM-PA-D37/HW/C300/DIO PWR - 2905651

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE front adapter, for Honeywell C300, Series C I/O, maximum of 1 x 16 channels can be connected (37-pos. D-SUB connector). Specifically for connecting digital, non-redundant I/O cards.

Why buy this product

- ✓ Specifically for non-redundant digital I/O cards
- ✓ Connection of a maximum of 16 digital channels
- ✓ Pre-assembled system cables are connected directly to I/O modules using the front adapters
- ✓ Front adapter with D-SUB connector

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. permissible current	1 A (per path)
Mounting position	any
Standards/regulations	DIN EN 50178
	IEC 60664

Front adapters - FLKM-PA-D37/HW/C300/DIO PWR - 2905651

Technical data

General

	IEC 62103
Degree of pollution	2
Overvoltage category	II

Connection data 1

Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

Supported controller


Controller	HONEYWELL Experion PKS C300/C-Series
- suitable I/O card	TDOB01 (non-redundant)
	TDOB11 (redundant)
	TDILA1
	TDODA1

Standards and Regulations

Standards/regulations	DIN EN 50178
	IEC 60664
	IEC 62103
Degree of pollution	2
Overvoltage category	II

Drawings

Circuit diagram



Connection scheme: FLKM-PA-D37/HW/DIO/C300

Classifications

eCl@ss

eCl@ss 5.1	27250313
------------	----------

Front adapters - FLKM-PA-D37/HW/C300/DIO PWR - 2905651

Classifications

eCl@ss

eCl@ss 6.0	27242608
eCl@ss 8.0	27249290
eCl@ss 9.0	27242292

ETIM

ETIM 5.0	EC002584
----------	----------

Approvals


Approvals


Approvals


UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705	
mm ² /AWG/kcmil	30-12
Nominal current IN	1 A
Nominal voltage UN	125 V

cUL Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 238705	
mm ² /AWG/kcmil	30-12
Nominal current IN	1 A
Nominal voltage UN	125 V

cULus Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	
--	--

