



Main

| | |
|------------------------|----------------|
| Range of Product | 9080G |
| Product Type | Terminal block |
| Localisation on Device | Standard |
| Color | Black |
| Quantity | Set of 50 |

Complementary

| | |
|---|---|
| Voltage Rating | 600 V AC/DC |
| Current Rating | 40 A CSA 70 A UL |
| Wire Size | AWG 22...AWG 10 copper |
| Mounting Type | Panel 9080GH track |
| Certifications | CSA file 62144 class 6228 01 CE UL recognized E60616 CCN XCFR2 |
| Electrical Connection | Copper box lugs |
| Material | Nylon block |
| Ambient Air Temperature for Operation | -40...257 °F (-40...125 °C) |
| Electrical Connection Tightening Torque | Lug copper 11...12 lbf.in (1.24...1.36 N.m) : AWG 22...AWG 10 copper) |
| Height | 1.39 in (35.31 mm) |
| Width | 1.4 in (35.56 mm) |
| Depth | 0.35 in (8.89 mm) |
| Density | 35 per foot |
| Compatible End Barrier | GK6B |

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 21702-9080 G (NOT GCB) |
| Discount Schedule | CP5 |
| GTIN | 785901744528 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.42 oz (11.793 g) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 3.81 in (9.677 cm) |
| Package 1 width | 10.16 in (25.806 cm) |
| Package 1 Length | 17.78 in (45.161 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|