

# Industrial Grade Secure Digital Cards

## *W7SDxxxx1XA-H60Px Series*

**INFORMATION IN THIS DOCUMENT IS PROVIDED IN RELATION TO WINTEC INDUSTRIES PRODUCTS, AND IS SUBJECT TO CHANGE WITHOUT NOTICE.**

**NOTHING IN THIS DOCUMENT SHALL BE CONTRUED AS GRANTING ANY LICENSE, EXPRESS OR IMPLIED.**

**ALL INFORMATION IN THIS DOCUMENT IS PROVIDED ON AN “AS-IS” BASIS WITHOUT GUARANTEE OR WARRANTY OF ANY KIND.**

- Please contact your nearest Wintec representative for the latest updates or additional product information.

## Revision History

Revision	Month	Year	History
1.0	January	2009	-Preliminary Release
1.1	February	2010	-Updated Ordering Guide

# Secure Digital Card

W7SDxxxx1XA-H60Px ROHS Compliant

## Features

### GENERAL

- Density up to 8GB
- 32-bit RISC/DSP Controller
- Solid State Data Storage
- Dual 3.3V / 1.8V Interface
- Industry Standard Compatibility
- ROHS Compliant

### PERFORMANCE

- High Performance 24 MB/s (Sustained Read)
- High Performance 23 MB/s (Sustained Write)
- Dual Channel operation
- Low Power Consumption

### RELIABILITY

- > 2,000,000 Program/Erase Cycles
- Industrial Wear Leveling
  - Includes Static Block Management
- Spares & Bad Block Management
- On-chip ECC and CRC16 unit for flash data protection
- Hardware support for CPRM

### COMPATIBILITY

- SD standard, rev. 1.01 / 1.10 / 2.0

## Description

The Wintec Industries W7SDxxxx1XA-H60Px series of ROHS Compliant Secure Digital Cards are constructed with Samsung NAND-type single-level-cell (SLC) flash memory devices paired to a powerful 32-bit RISC/DSP-based system controller for virtual-to-physical address mapping and other flash management functions.

Wintec Secure Digital Cards employ a variety of sophisticated error checking and flash management utilities allowing for maximum levels of data reliability and card endurance. Patented wear-leveling methods ensure even wear of flash blocks across the entire card capacity. Background operations track erase counts, prioritize new writes to blocks with lower wear, and relocate static data to blocks with higher wear. Bad-block Management routines replace worn



Wintec Secure Digital Card

blocks with spare blocks reserved by the controller on card initialization. Reed-Solomon based ECC algorithms capable of correcting 4 bytes in a 512 byte sector are implemented on the fly without performance degradation to ensure data reliability through user data transfers and background wear-leveling operations. Additional information regarding the specifics of wear leveling, ECC methods, and application-specific card life calculations are available upon request and under NDA.

## 1.0 General Product Specification

For all the following specifications, values are defined at ambient temperature and nominal supply voltage unless otherwise stated.

**Table 1: Performance Specifications**

Parameter		Spec
<b>Burst Transfer Rate To/From Host: Read</b>		24 MB/s
<b>Write</b>		23 MB/s
<b>Burst Transfer Rate To/From Flash</b>		40.0 MB/s per channel
<b>Active-to-Sleep Delay after processing the last command</b>		0 s
<b>Startup Times</b>	<b>Sleep-to-Write (Max.)</b>	No Delay
	<b>Sleep-to-Read (Max.)</b>	No Delay
	<b>Reset-to-Ready (Typical)</b>	100.0 ms
	<b>Reset-to-Ready (Max.)</b>	500.0 ms

**Table 2: Card Endurance**

Parameter	Spec
<b>Program/Erase Cycles</b>	> 2,000,000 Cycles
<b>Read Cycles</b>	Unlimited
<b>Data Retention</b>	10 Years (Min.)

**Table 3: Card Data Reliability**

Parameter	Spec
<b>Non-Recoverable Errors</b>	< 1 in 10 <sup>20</sup> Bytes Read
<b>Erroneous Correction</b>	< 1 in 10 <sup>20</sup> Bytes Read
<b>ECC Correctability</b>	4 Random Bytes/Sector

**Table 4: Environmental Specifications**

Parameters	Operating	Non-Operating
<b>Temperature (Commercial Temp)</b>	0°C to 70°C	-40°C to 125°C
<b>Temperature (Extended Temp)</b>	-25°C to 85°C	-40°C to 125°C
<b>Relative Humidity</b>	25% to 95% (Non-Condensing)	40% to 93% (Non-Condensing)
<b>Vibration</b>	15 G rms	15 G rms
<b>Altitude</b>	80,000 ft. (Max.)	N/A
<b>Shock</b>	1,000 G (Max.)	1,000 G (Max.)
<b>Acoustic</b>	0 db	N/A

**NOTE:**

1. Input voltage 3.3V (±5%) or 1.8V (±10%) with a maximum ripple of 100mV peak-to-peak.
2. All values listed are at 25°C and nominal supply voltage.
3. Stated figures are based on primary configurations and may vary as larger density component NAND flashes are released.

## 2.0 Architecture




Figure 1: Card Block Diagram

Table 5: Card Pin Assignment

PIN NO	NAME	TYPE	DESCRIPTION
1	CD/DAT	I/O/PP3	Card Detect/Data Line [Bit3]
2	CMD	PP	Command / Response
3	VSS1	S	Supply voltage ground
4	VDD	S	Supply voltage
5	CLK	I	Clock
6	VSS2	S	Supply voltage ground
7	DAT0	I/O/PP	Data Line [Bit0]
8	DAT1	I/O/PP	Data Line [Bit1]
9	DAT2	I/O/PP	Data Line [Bit2]

- 1) S : power supply ; I : input ; O : output ; PP : push-pull ; OD : open-drain NC : Not connected (or logical high)  
2) The DAT line for read - when card is in output mode only

### 3.0 Ordering Information

**Table 6: Product Availability List & Naming**

Card Capacity	Part Number
128 MB	W7SD128M1XA(I)-H60PC-002.01
256 MB	W7SD256M1XA(I)-H60PB-002.01
512 MB	W7SD512M1XA(I)-H60PB-002.01
1 GB	W7SD001G1XA(I)-H60PB-002.01
2 GB	W7SD002G1XA(I)-H60PB-02D.01
4 GB	W7SD004GHXA(I)-H60PB-2Q2.01
8 GB	W7SD008GHXA(I)-H60PB-2Q2.01

### Contact Us (US & Int'l)

Wintec Industries OEM Sales  
675 Sycamore Drive,  
Milpitas, CA 95035  
Ph: 408-856-0500  
Fx: 408-856-0518

[oemsales@wintecind.com](mailto:oemsales@wintecind.com)  
<http://www.wintecind.com/oem>

### About Wintec Industries, Inc.

Wintec, founded in 1988, is headquartered in Milpitas, California. Wintec, a leading third party memory module manufacturer, specializes in a variety of module design and manufacturing, such as memory module, flash module, Handspring module, modem module, game module, etc. Besides a complete line of DDR, SDR, and EDO/FPM legacy memory modules, Wintec also distribute CPU, motherboard, peripherals, PC software, and consumer Flash products (such as MMC, SD, SMC, CompactFlash, PC Card, etc.). With excellent design engineering and manufacturing capability, Wintec provides a wide range of design and manufacturing services for our valuable customers from concept design to final product delivery. Wintec is ISO9001-2000 certified.

### Important Notice

Wintec Industries, Inc. makes no representations or warranties with respect to the contents of this User Guide and specifically disclaims any implied warranties of any product design for any particular purpose. Wintec Industries, Inc. reserves the rights to revise this publication and to make changes from time to time in the content hereof without obligation of Wintec Industries, Inc. to notify any person or organization of such revisions or changes.