

**Data sheet | Item number: 753-467**

2-channel analog input; 0 ... 10 VDC; Single-ended

[www.wago.com/753-467](http://www.wago.com/753-467)



**Color:**




Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Item description

This analog input module processes standard 0–10 V signals.

The input signal is electrically isolated and is transmitted with a resolution of 12 bits.

The internal system supply powers the module.

The input channels of the module have a common ground potential.

The shield directly connects to the DIN-rail.

Subject to changes. Please also observe the further product documentation!



## Data Notes

|      |  |
|------|--|
| Note | Pluggable connectors and coding fingers (753 Series) are not included. |
|------|--|

## Technical data

|  |  |
|--|--|
| Number of analog inputs  | 2  |
| Total number of channels (module)                              | 2  |
| Signal type  | Voltage  |
| Signal type (voltage)  | 0 ... 10 VDC   |
| Sensor connection  | 2 x (2-wire)   |
| Input voltage (max.)   | 35 V   |
| Signal characteristics   | Single-ended   |
| Resolution [bit]   | 12 bits  |
| Data width   | 2 x 16-bit data; 2 x 8-bit control/status (optional) |
| Internal resistance  | 130 k $\Omega$                                       |
| Conversion time (typ.)   | 2 ms   |
| Measurement error (reference temperature)                      | 25 °C  |
| Measurement error, deviation (max.) from the upper-range value | 0.2 %  |
| Temperature error (max.) of the upper-range value              | 0.01 %/K   |
| Supply voltage (system)  | 5 VDC; via data contacts                             |
| Current consumption (5 V system supply)                        | 60 mA  |
| Isolation  | 500 V system/field                                   |
| Indicators   | LED (A, C) green: Function AI 1, AI 2                |

## Connection data

|                                       |  |
|---------------------------------------|--|
| Connection technology: inputs/outputs | 8 x CAGE CLAMP®                              |
| Connection type 1                     | Inputs/Outputs                               |
| Solid conductor                       | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Fine-stranded conductor               | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Strip length                          | 9 ... 10 mm / 0.35 ... 0.39 inches           |

Subject to changes. Please also observe the further product documentation!



## Physical data

|                                   |                        |
|-----------------------------------|------------------------|
| Width                             | 12 mm / 0.472 inches   |
| Height                            | 100 mm / 3.937 inches  |
| Depth                             | 69.8 mm / 2.748 inches |
| Depth from upper-edge of DIN-rail | 62.6 mm / 2.465 inches |

## Mechanical Data

|                     |             |
|---------------------|-------------|
| Mounting type       | DIN-35 rail |
| Pluggable connector | Pluggable   |

## Material Data

|                    |                              |
|--------------------|------------------------------|
| Color              | light gray                   |
| Housing material   | Polycarbonate; polyamide 6.6 |
| Fire load          | 0.882 MJ                     |
| Weight             | 40 g                         |
| Conformity marking | CE                           |

## Environmental requirements

|  |                                       |
|--|---------------------------------------|
| Ambient temperature (operation)  | 0 ... +55 °C                          |
| Ambient temperature (storage)  | -40 ... +85 °C                        |
| Protection type  | IP20                                  |
| Pollution degree   | 2 per IEC 61131-2                     |
| Operating altitude   | 0 ... 2000 m / 0 ... 6562 ft          |
| Mounting position  | horizontal (standing/lying); vertical |
| Relative humidity (without condensation)   | 95 %                                  |
| Vibration resistance   | per IEC 60068-2-6                     |
| Shock resistance   | 15g per IEC 60068-2-27                |
| EMC immunity to interference   | per EN 61000-6-2                      |
| EMC emission of interference   | per EN 61000-6-4                      |
| Exposure to pollutants   | Per IEC 60068-2-42 and IEC 60068-2-43 |
| Permissible H <sub>2</sub> S contaminant concentration at a relative humidity 75 % | 10 ppm                                |
| Permissible SO <sub>2</sub> contaminant concentration at a relative humidity 75 %  | 25 ppm                                |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



## Commercial data

|                       |                 |
|-----------------------|-----------------|
| Product Group         | 15 (I/O System) |
| eCl@ss 10.0           | 27-24-26-01     |
| eCl@ss 9.0            | 27-24-26-01     |
| ETIM 8.0              | EC001596        |
| ETIM 7.0              | EC001596        |
| Recupel Type          |                 |
| PU (SPU)              | 1 pcs           |
| Packaging type        | box             |
| Country of origin     | DE              |
| GTIN                  | 4045454394486   |
| Customs tariff number | 85389099990     |

## Environmental Product Compliance

|   |   |
|---|---|
| CAS-No.                                   | 1303-86-2<br>1317-36-8<br>25550-51-0<br>7439-92-1   |
| REACH Candidate List Substance            | 4-Methyl-1,2-cyclohexanedicarboxylic anhydride<br>Diboron trioxide<br>Lead<br>Lead monoxide |
| RoHS Compliance Status                    | Compliant,With Exemption  |
| RoHS Exemption                            | 6(c)<br>7(a)<br>7(c)-I<br>7(c)-II   |
| SCIP notification number (Austria)        | 17daabe6-8ae6-4530-b300-d57a9b24de41  |
| SCIP notification number (Belgium)        | b3f1c3ad-5eb0-4578-bc0a-2f9bcef302d9  |
| SCIP notification number (Bulgaria)       | fca1075c-04c4-4bf1-a1d4-474daeb3a023  |
| SCIP notification number (Czech Republic) | e2e54317-76f8-4363-8c6c-03d65966f216  |
| SCIP notification number (Denmark)        | 2ea724bb-8a2b-4412-8677-dba87838dfe0  |
| SCIP notification number (Finland)        | b29ded38-abad-431c-923a-2f37649a1bcd  |
| SCIP notification number (France)         | 073a340c-d083-4b17-8f46-17425d5e36f0  |
| SCIP notification number (Germany)        | fc29d354-7458-4a1a-9a1a-4a5f56d4209a  |
| SCIP notification number (Hungary)        | 03f500ee-b556-4001-87d4-3defa3b8b88a  |
| SCIP notification number (Italy)          | 03f9e91b-277c-4b7e-8512-aef1c4087032  |
| SCIP notification number (Netherlands)    | 1e387295-0273-4e4d-8a62-4abd51925f18  |
| SCIP notification number (Poland)         | 4c8b541a-aef1-4f18-9444-7ae27d3fdaa5  |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



|                                    |                                      |
|------------------------------------|--------------------------------------|
| SCIP notification number (Romania) | 8bb4f35c-7280-47f5-9ac8-96a261f144e4 |
| SCIP notification number (Sweden)  | 22695d31-16d7-4fa5-9e0f-409ef56e66e5 |

## Approvals / Certificates

### General approvals

| Logo | Approval   | Additional Approval Text | Certificate name            |
|------|--|--------------------------|-----------------------------|
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle                    | TP TC 020/2011           | EAC RU C-DE.AM02.B.00087/19 |
|      | <b>KC</b><br>National Radio Research Agency                      | Article 58-2, Clause 3   | MSIP-REM-W43-AIM750         |
|      | <b>UL</b><br>Underwriters Laboratories Inc. (ORDINARY LOCATIONS) | UL 508                   | E175199 Sec.1               |

### Declarations of conformity and manufacturer's declarations

| Logo | Approval  | Additional Approval Text | Certificate name |
|------|---|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |
|      | <b>UK-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

### Approvals for hazardous areas

| Logo | Approval  | Additional Approval Text | Certificate name                                 |
|------|---|--------------------------|--|
|      | <b>ATEX</b><br>TUEV Nord Cert GmbH                                | EN 60079-0               | TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc)       |
|      | <b>CCCEX</b><br>CQST/CNEX   | CNCA-C23-01              | 2020312310000213 (Ex ec IIC T4 Gc)               |
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle                     | TP TC 012/2011           | EAC RU C-DE.AM02.B.00163/19 (2Ex nA IIC T4 Gc X) |
|      | <b>IECEX</b><br>TUEV Nord Cert GmbH                               | IEC 60079-0              | IECEX TUN 14.0035 X (Ex ec IIC T4 Gc)            |
|      | <b>INMETRO</b><br>TÜV Rheinland do Brasil Ltda.                   | IEC 60079-0              | BR-Ex_TÜV 12.1297 X                              |
|      | <b>UKEx</b><br>WAGO GmbH & Co. KG                                 | EN 60079-0               | UKCA_WAGO22UKEX003X_ec                           |
|      | <b>UL</b><br>Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS) | UL 121201                | E198726 Sec.1                                    |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Required accessories

### Pluggable connector

Male connector/plug

**Item no.: 753-110**  
Plug

[www.wago.com/753-110](http://www.wago.com/753-110)

## Optional accessories

### Shield termination

Shield clamping saddles

**Item no.: 790-116**  
Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm

[www.wago.com/790-116](http://www.wago.com/790-116)

**Item no.: 790-124**  
Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm

[www.wago.com/790-124](http://www.wago.com/790-124)

**Item no.: 790-108**  
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm

[www.wago.com/790-108](http://www.wago.com/790-108)

**Item no.: 790-140**  
Shield clamping saddle; diameter of compatible conductor

[www.wago.com/790-140](http://www.wago.com/790-140)

**Item no.: 790-216**  
Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm

[www.wago.com/790-216](http://www.wago.com/790-216)

**Item no.: 790-220**  
Shield clamping saddle; 30 mm wide; 6 ... 20 mm

[www.wago.com/790-220](http://www.wago.com/790-220)

**Item no.: 790-208**  
Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm

[www.wago.com/790-208](http://www.wago.com/790-208)

### Pluggable connector

Coding

**Item no.: 753-150**  
753 Series coding elements

[www.wago.com/753-150](http://www.wago.com/753-150)

### Carrier rail

Mounting accessories

**Item no.: 210-197**  
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored

[www.wago.com/210-197](http://www.wago.com/210-197)

**Item no.: 210-198**  
Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored

[www.wago.com/210-198](http://www.wago.com/210-198)

**Item no.: 210-504**  
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored

[www.wago.com/210-504](http://www.wago.com/210-504)

**Item no.: 210-505**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



|  |  |
|--|--|
| Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored                                  | <a href="http://www.wago.com/210-505">www.wago.com/210-505</a> |
| <b>Item no.: 210-506</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored       | <a href="http://www.wago.com/210-506">www.wago.com/210-506</a> |
| <b>Item no.: 210-508</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored         | <a href="http://www.wago.com/210-508">www.wago.com/210-508</a> |
| <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                  | <a href="http://www.wago.com/210-113">www.wago.com/210-113</a> |
| <b>Item no.: 210-118</b><br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                 | <a href="http://www.wago.com/210-118">www.wago.com/210-118</a> |
| <b>Item no.: 210-112</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored | <a href="http://www.wago.com/210-112">www.wago.com/210-112</a> |
| <b>Item no.: 210-114</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored                   | <a href="http://www.wago.com/210-114">www.wago.com/210-114</a> |
| <b>Item no.: 210-115</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored | <a href="http://www.wago.com/210-115">www.wago.com/210-115</a> |
| <b>Item no.: 210-196</b><br>Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored               | <a href="http://www.wago.com/210-196">www.wago.com/210-196</a> |

**Marking accessories**

|   |  |
|---|--|
| Marker carrier  |  |
| <b>Item no.: 750-103</b><br>Group marker carrier  | <a href="http://www.wago.com/750-103">www.wago.com/750-103</a>                   |
| Marker  |  |
| <b>Item no.: 2009-145/000-006</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue   | <a href="http://www.wago.com/2009-145/000-006">www.wago.com/2009-145/000-006</a> |
| <b>Item no.: 2009-145</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white          | <a href="http://www.wago.com/2009-145">www.wago.com/2009-145</a>                 |
| <b>Item no.: 2009-145/000-002</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow | <a href="http://www.wago.com/2009-145/000-002">www.wago.com/2009-145/000-002</a> |
| <b>Item no.: 2009-145/000-007</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray   | <a href="http://www.wago.com/2009-145/000-007">www.wago.com/2009-145/000-007</a> |
| <b>Item no.: 2009-145/000-005</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red    | <a href="http://www.wago.com/2009-145/000-005">www.wago.com/2009-145/000-005</a> |

Subject to changes. Please also observe the further product documentation!





|   |  |
|---|--|
| <b>Item no.: 2009-145/000-012</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/2009-145/000-012">www.wago.com/2009-145/000-012</a> |
| <b>Item no.: 2009-145/000-023</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green  | <a href="http://www.wago.com/2009-145/000-023">www.wago.com/2009-145/000-023</a> |
| <b>Item no.: 2009-145/000-024</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet | <a href="http://www.wago.com/2009-145/000-024">www.wago.com/2009-145/000-024</a> |
| <b>Item no.: 248-501/000-006</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue                                    | <a href="http://www.wago.com/248-501/000-006">www.wago.com/248-501/000-006</a>   |
| <b>Item no.: 248-501/000-007</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray                                    | <a href="http://www.wago.com/248-501/000-007">www.wago.com/248-501/000-007</a>   |
| <b>Item no.: 248-501/000-002</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow                                  | <a href="http://www.wago.com/248-501/000-002">www.wago.com/248-501/000-002</a>   |
| <b>Item no.: 248-501/000-012</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange                                  | <a href="http://www.wago.com/248-501/000-012">www.wago.com/248-501/000-012</a>   |
| <b>Item no.: 248-501</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white   | <a href="http://www.wago.com/248-501">www.wago.com/248-501</a>                   |
| <b>Item no.: 248-501/000-017</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green                             | <a href="http://www.wago.com/248-501/000-017">www.wago.com/248-501/000-017</a>   |
| <b>Item no.: 248-501/000-005</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red                                     | <a href="http://www.wago.com/248-501/000-005">www.wago.com/248-501/000-005</a>   |
| <b>Item no.: 248-501/000-024</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet                                  | <a href="http://www.wago.com/248-501/000-024">www.wago.com/248-501/000-024</a>   |
| <b>Item no.: 248-501/000-023</b><br>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green                                   | <a href="http://www.wago.com/248-501/000-023">www.wago.com/248-501/000-023</a>   |
| <b>Item no.: 750-100</b><br>Marker card; as a DIN A4 sheet; plain   | <a href="http://www.wago.com/750-100">www.wago.com/750-100</a>                   |
| Group marker carrier  |  |
| <b>Item no.: 750-106</b><br>Group marker carrier  | <a href="http://www.wago.com/750-106">www.wago.com/750-106</a>                   |

Subject to changes. Please also observe the further product documentation!



## System housing

## System enclosure

|  |  |
|--|--|
| <b>Item no.: 850-814/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate                 | <a href="http://www.wago.com/850-814/002-000">www.wago.com/850-814/002-000</a> |
| <b>Item no.: 850-815/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate                 | <a href="http://www.wago.com/850-815/002-000">www.wago.com/850-815/002-000</a> |
| <b>Item no.: 850-816/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate                 | <a href="http://www.wago.com/850-816/002-000">www.wago.com/850-816/002-000</a> |
| <b>Item no.: 850-817/002-000</b><br>IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate                 | <a href="http://www.wago.com/850-817/002-000">www.wago.com/850-817/002-000</a> |
| <b>Item no.: 850-825</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20                               | <a href="http://www.wago.com/850-825">www.wago.com/850-825</a>                 |
| <b>Item no.: 850-826</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip          | <a href="http://www.wago.com/850-826">www.wago.com/850-826</a>                 |
| <b>Item no.: 850-827</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip          | <a href="http://www.wago.com/850-827">www.wago.com/850-827</a>                 |
| <b>Item no.: 850-827/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip  | <a href="http://www.wago.com/850-827/002-000">www.wago.com/850-827/002-000</a> |
| <b>Item no.: 850-826/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip  | <a href="http://www.wago.com/850-826/002-000">www.wago.com/850-826/002-000</a> |
| <b>Item no.: 850-828/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip | <a href="http://www.wago.com/850-828/002-000">www.wago.com/850-828/002-000</a> |
| <b>Item no.: 850-828</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip         | <a href="http://www.wago.com/850-828">www.wago.com/850-828</a>                 |
| <b>Item no.: 850-834</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20                               | <a href="http://www.wago.com/850-834">www.wago.com/850-834</a>                 |
| <b>Item no.: 850-835</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip          | <a href="http://www.wago.com/850-835">www.wago.com/850-835</a>                 |
| <b>Item no.: 850-836</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip          | <a href="http://www.wago.com/850-836">www.wago.com/850-836</a>                 |

Subject to changes. Please also observe the further product documentation!



## Downloads

### Documentation

#### Manual

|  |                         |               |          |
|--|-------------------------|---------------|----------|
| System Manual WAGO I/O System 750/753<br>Decentralized Automation Technology | V 3.3.3<br>2023 年8月29 日 | pdf<br>8.7 MB | Download |
|--|-------------------------|---------------|----------|

|   |         |               |          |
|---|---------|---------------|----------|
| Product Manual 2-channel, 0-10VDC, single-ended | V 1.1.0 | pdf<br>3.9 MB | Download |
|---|---------|---------------|----------|

|   |  |     |          |
|---|--|-----|----------|
| System Manual Series 750/753<br>Online HTML |  | URL | Download |
|---|--|-----|----------|

#### Instruction Leaflet

|  |              |                 |          |
|--|--------------|-----------------|----------|
| CCC Ex (Additional information)<br>WAGO-I/O-SYSTEM *750-****/* | 2023 年4月26 日 | pdf<br>163.6 kB | Download |
|--|--------------|-----------------|----------|

#### System Description

|   |  |                 |          |
|---|--|-----------------|----------|
| 750/753 Series I/O-System – General Product Information |  | pdf<br>976.2 kB | Download |
|---|--|-----------------|----------|

|   |  |                 |          |
|---|--|-----------------|----------|
| Overview on WAGO-I/O-SYSTEM 750 approvals |  | pdf<br>223.5 kB | Download |
|---|--|-----------------|----------|

#### Additional Information

|   |                         |               |          |
|---|-------------------------|---------------|----------|
| Disposal and Recycling<br>Electrical and electronic equipment, Batteries, Packaging | V 1.1.0<br>2022 年8月18 日 | pdf<br>2.2 MB | Download |
|---|-------------------------|---------------|----------|

## CAD/CAE-Data

### CAD data

|                      |  |     |          |
|----------------------|--|-----|----------|
| 2D/3D Models 753-467 |  | URL | Download |
|----------------------|--|-----|----------|

### CAE data

|                           |  |     |          |
|---------------------------|--|-----|----------|
| EPLAN Data Portal 753-467 |  | URL | Download |
|---------------------------|--|-----|----------|

|                        |  |     |          |
|------------------------|--|-----|----------|
| WSCAD Universe 753-467 |  | URL | Download |
|------------------------|--|-----|----------|

ZUKEN Portal 753-467

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



[URL](#)

[Download](#)

---

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 753-467

[URL](#)

[Download](#)

2-channel analog input; 0 ... 10 VDC; Single-ended

---

## Installation Notes

### Product family

**WAGO I/O System 750/753**

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.