

Han TC300 female contact M8, short



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Part number | 09 11 000 6679 |
| Specification | Han TC300 female contact M8, short |
| HARTING eCatalogue | https://b2b.harting.com/09110006679 |

Identification

| | |
|----------------------------|---------------------|
| Category | Contacts |
| Series | TC 300 |
| Type of contact | Screw contact |
| Description of the contact | M8 Short version |

Version

| | |
|-----------------------|-----------------|
| Gender | Female |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|----------------------|-----------------|
| Operating current | ≤300 A |
| Contact resistance | ≤0.3 mΩ |
| Tightening torque | 10 Nm |
| Wrench size | 5 14 |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|---------------------|---------------|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Silver plated |



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------------|-------------|
| Specifications | IEC 60664-1 |
| | IEC 61984 |

Commercial data

| | |
|--------------------------------|--------------------------------------------|
| Packaging size | 1 |
| Net weight | 47.17 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140188549 |
| eCl@ss | 27440204 Contact for industrial connectors |