

# Han 16HPR EasyCon cover 4XM25 for Female



| Part number        | 19 40 016 9902                              |
|--------------------|---|
| Specification      | Han 16HPR EasyCon cover 4XM25 for<br>Female |
| HARTING eCatalogue | https://b2b.harting.com/19400169902         |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category                    | Hoods/Housings                                |
|-----------------------------|---|
| Series of hoods/housings    | Han <sup>®</sup> HPR EasyCon                  |
| Type of hood/housing        | Mounting cover                                |
| Description of hood/housing | for surface mounted housings<br>for hoods     |
| Version                     |   |
| Size                        | 16 HPR  |
| Cable entry                 | 4x M25  |
| Locking type                | Screw locking                                 |
| Field of application        | Hoods/housings for harsh outdoor environments |

#### **Technical characteristics**

Details

| Tightening torque                      | 6 Nm Mounting cover<br>6 Nm Distance bolt<br>6 Nm Fixing screws |
|--|---|
| Limiting temperature                   | -40 +125 °C   |
| Note on the limiting temperature       | For use as a connector according to IEC 61984.                  |
| Degree of protection acc. to IEC 60529 | IP65<br>IP68<br>IP69 / IPX9K acc. to ISO 20653                  |

Not compatible to cable glands 19 00 000 5013 and 19 00 000 5019

Page 1 / 2 | Creation date 2023-06-28 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### **Technical characteristics**

|                                    | 4  |
|------------------------------------|----|
| Type rating acc. to UL 50 / UL 50E | 4X |
|                                    | 12 |

## Material properties

| Material (hood/housing)              | Aluminium die-cast<br>Corrosion resistant |
|--------------------------------------|---|
| Surface (hood/housing)               | Powder-coated                             |
| Colour (hood/housing)                | RAL 9005 (jet black)                      |
| Material (seal)                      | NBR                                       |
| RoHS                                 | compliant                                 |
| ELV status                           | compliant                                 |
| China RoHS                           | e   |
| REACH Annex XVII substances          | Not contained                             |
| REACH ANNEX XIV substances           | Not contained                             |
| REACH SVHC substances                | Not contained                             |
| California Proposition 65 substances | Yes                                       |
| California Proposition 65 substances | Naphthalene                               |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)                      |
| Requirement set with Hazard Levels   | R1 (HL 1-3)<br>R7 (HL 1-3)                |

### Specifications and approvals

| UL / CSA                       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
|--------------------------------|--|
| Approvals                      | DNV GL   |
| Commercial data                |  |
| Packaging size                 | 1  |
| Net weight                     | 199.1 g  |
| Country of origin              | China  |
| European customs tariff number | 85389099   |
| GTIN                           | 5713140175242  |
| eCl@ss                         | 27440202 Shell for industrial connectors                   |

Page 2 / 2 | Creation date 2023-06-28 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com