


## VS-ST-KX-75-LP

Order No.: 1655645



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655645>

Coaxial contact, for D-SUB combination inserts, for PCB assembly,  
pin, angled, gold-plated

Commercial data	
GTIN (EAN)	 4 046356 029537
Note	Made-to-order
sales group	D502
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 325 (PC-2009)

### Product notes

WEEE/RoHS-compliant since:  
09/07/2006



[http://  
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given  
here has been taken from the  
online catalog. For comprehensive  
information and data, please refer  
to the user documentation. The  
General Terms and Conditions of  
Use apply to Internet downloads.

### Technical data

Mechanical characteristics	
Insertion/withdrawal cycles	≥ 500

Type of connection	PCB mounting
Insertion force per signal contact	≤ 7.00 N
Extraction force per signal contact	≤ 7 N
Ambient temperature (operation)	-55 °C ... 135 °C

#### Material data

Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

#### Electrical characteristics

Rated voltage (III/3)	250 V
Rated current	2 A
Insulation resistance	10 TΩ

#### Accessories

Item	Designation	Description
1676747	HC-M4-KOAX-EWZ	Contact removal tool for coaxial contacts

#### Tools

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;