

DIMENSION


L	Nx10,0-2.5
P	(N-1)x10,0

N=Number of poles

Poles	DIM L	Tolerance	DIM P
2p-4p	±0.20	±0.20	±0.20
5p-8p	±0.30	±0.30	±0.30
9p-12p	±0.40	±0.40	±0.40

Material
 Terminal body: steel stamping clamp Zinc plating
 Terminal screw: Steel Zinc plating "-" slot type
 Solder pin: Brass, Tin plated
 Firm wire chunk: steel Zinc plating
 Terminal housing: Thermoplastic (UL94V-0)
 GREEN(RAL6018/T)
 Terminal cover: Thermoplastic(UL94V-0)
 GREEN(RAL6018/T)

Electrical cULus
 Voltage rating: 300VAC
 Current rating: 20A
 Wire range:
 Solid wire(AWG): 12-22
 Stranded wire(AWG): 12-22
 Torque(Lb-In): 2.4
 Screw: M2.5
 Wire strip length: 10-11mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval: **PA** us

RoHS compliant
 Unit: mm

 File No.: E349947

Scale	Free	Id.	Modification	Date	Name
TOLERANCE					
X.	±0.50			19.04.2010	Alex
X.X	±0.30				
X.XX	±0.10				
DIM	TOL				
X.°	±1°				
Angle	TOL				

Date	Name	Customer-No.	Drawing-No.	Replace	Sheet
19.04.2010	Alex				
15.03.2016	Amy	ASSMANN WSW-No.	A-TB100-TRXXV	ASS 4100 CO	rev01

ASSMANN
 WSW components

1	2	3	4	5	6	7
H	G	F	E	D	C	B