




Straight power contacts for cable applications

Identification	Rating (A)	Part number	
Performance levels 		Performance level 3	S4 ¹⁾
Solder version Male contacts Short male contacts Female contacts Short female contacts	10 20 30 40 20 40 10 20 30 40 20 40	09 69 281 7420 09 69 281 7421 09 69 281 7422 09 69 281 7423 09 69 281 7821 09 69 281 7823 09 69 181 7420 09 69 181 7421 09 69 181 7422 09 69 181 7423 09 69 181 7821 09 69 181 7823	09 69 281 5420 09 69 281 5421 09 69 281 5422 09 69 281 5423 09 69 281 5821 09 69 281 5823 09 69 181 5420 09 69 181 5421 09 69 181 5422 09 69 181 5423 09 69 181 5821 09 69 181 5823
Crimp version ²⁾ Male contacts Short male contacts Female contacts Short female contacts	10 20 30 40 20 40 10 20 30 40 20 40	09 69 282 7420 09 69 282 7421 09 69 282 7422 09 69 282 7423 09 69 282 7821 09 69 282 7823 09 69 182 7420 09 69 182 7421 09 69 182 7422 09 69 182 7423 09 69 182 7821 09 69 182 7823	09 69 282 5420 09 69 282 5421 09 69 282 5422 09 69 282 5423 09 69 282 5821 09 69 282 5823 09 69 182 5420 09 69 182 5421 09 69 182 5422 09 69 182 5423 09 69 182 5821 09 69 182 5823

D-Sub

¹⁾ S4 = 0.76 µm Au or PdNi equivalent
²⁾ Tooling see chapter 20