


FLK 16/14/DV-OUT/400

Order No.: 2305198

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305198>

Assembled round cable, with one 16-pos. and one 14-pos. socket strip
(for Emerson Delta V), cable length: 4 m

Commercial data

| | |
|----------------|---|
| GTIN (EAN) |  4 046356 038911 |
| Note | Made-to-order |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |

Product notes

WEEE/RoHS-compliant since:
08/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

| | |
|---|------------------|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Number of positions, control side | 16 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 14 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 4 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Single wire, material | Cu tin-plated |
| External diameter | 7 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;