

Hybrid cable - VS-M12MS-94H-HYB/15,0 SCO - 1402446

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Assembled Ethernet cable, CAT5e, shielded, 8-wire, 4 x 26 AWG (data) and 4 x 20 AWG (power), RAL 9005 (black), M12 hybrid plug to free cable end, length: 15.0 m



Key commercial data

| | |
|------------------------|---|
| Packing unit | 0 |
| Minimum order quantity | 1 |
| Catalog page | Page 323 (PC-2011) |
| GTIN |  4 046356 616034 |
| Custom tariff number | 85444210 |
| Country of origin | GERMANY |

Technical data

General data

| | |
|-----------------------|-----------------------|
| Rated current at 40°C | 6 A (Power) |
| Rated current at 40°C | 0.5 A (Data) |
| Rated voltage | 30 V (Power and data) |
| Number of positions | 8 |
| Length of cable | 15 m |

General characteristics

| | |
|----------------------|------------------------------|
| Coding | Y - hybrid |
| Pollution degree | 2 |
| Degree of protection | IP67/IP69K |
| Material, knurls | Zinc die-cast, nickel-plated |
| Status display | No |

Conductor data

| | |
|---------------------------|----------------------------------|
| Cable type | Ethernet hybrid |
| Cable type (abbreviation) | 94H |
| Cable structure | 1x4xAWG26+1x4xAWG20 |
| Conductor cross section | 4x 0.15 mm ² (Signal) |

Hybrid cable - VS-M12MS-94H-HYB/15,0 SCO - 1402446

Technical data

Conductor data

| | |
|---|---|
| Conductor cross section | 4x 0.6 mm ² (Power) |
| AWG signal line | 26 |
| AWG power supply | 20 |
| Conductor structure signal line | 19x 0.10 mm |
| Conductor structure, voltage supply | 19x 0.20 mm |
| Core diameter including insulation | 1.15 mm (Signal) |
| Core diameter including insulation | 1.4 mm (Power) |
| Wire colors | White/orange-orange, white/green-green, white, blue, brown, black |
| External sheath, color | Black RAL 9005 |
| External cable diameter D | 7.6 mm |
| Smallest bending radius, movable installation | min. 76 mm |
| Outer sheath, material | PUR mixture halogen-free |
| Conductor material | Bare Cu litz wires |
| Wave impedance | 100 Ω ± 15 Ω (At an ambient temperature of 20°C) |

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27259205 |
| eCl@ss 6.0 | 27269202 |
| eCl@ss 7.0 | 27449203 |

etim

| | |
|----------|----------|
| ETIM 4.0 | EC002599 |
|----------|----------|


unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 26121616 |
| UNSPSC 7.0901 | 26121616 |
| UNSPSC 11 | 26121604 |
| UNSPSC 12.01 | 26121616 |
| UNSPSC 13.2 | 26121616 |

Drawings

Hybrid cable - VS-M12MS-94H-HYB/15,0 SCO - 1402446


Dimensioned drawing



M12 connector, straight, shielded

Hybrid cable - VS-M12MS-94H-HYB/15,0 SCO - 1402446

Schematic diagram



Hybrid cable - VS-M12MS-94H-HYB/15,0 SCO - 1402446

Circuit diagram

