



har-flexicon male connector, vertical



General information

Design					
Type	male connector				
Type	har-flexicon 3.50/3.81 MTV	har-flexicon 5.00 MTV	har-flexicon 5.08 MTV	har-flexicon 3.50 MWV	har-flexicon 5.00/5.08 MWV
Part numbers	1412xx14001xxx & 1412xx14005xxx 1412xx15001xxx & 1412xx15005xxx	1412xx16001xxx	1412xx17001xxx 1412xx17005xxx	1413xx14001xxx	1413xx16001xxx 1413xx17001xxx
Contact pitch	3.50/3.81 mm	5 mm	5.08 mm	3.50 mm	5.00/5.08 mm
No. of contacts	2-25 poles	2-20 poles	2-22 poles	2 - 12 poles	2 - 12 poles
Rated surge voltage (II/2) ¹⁾	2.5 kV	4 kV	4 kV	2.5 kV	4 kV
Rated surge voltage (III/2) ²⁾	2.5 kV	4 kV	4 kV	2.5 kV	4 kV
Rated surge voltage (III/3) ³⁾	2.5 kV	4 kV	4 kV	2.5 kV	4 kV
Rated Voltage	300 V	300 V	300 V	300 V	300 V
Rated voltage (II/2) ⁴⁾	300 V	600 V	600 V	300 V	600 V
Rated voltage (III/2) ⁵⁾	150 V	300 V	300 V	150 V	300 V
Rated voltage (III/3) ⁶⁾	150 V	250 V	250 V	150 V	250 V
Working current	11 A	15 A	15 A	11 A	15 A
Usegroup B, rated voltage / current	300 V / 11 A	300 V / 15 A	300 V / 15 A	300 V / 11 A	300 V / 15 A
Usegroup C, rated voltage / current	- / -	- / -	- / -	- / -	- / -
Usegroup D, rated voltage / current	300 V / 11 A	300 V / 15 A	300 V / 15 A	300 V / 11 A	300 V / 15 A
Contact resistance	max. 15 mOhm				
Insulation resistance	min. 10 ⁹ Ohm (500 V DC)				
Temperature range	-40°C ... +110°C				
Termination technology	THR Reflow	THR Reflow	THR Reflow	wave soldering	wave soldering
Insertion force	max. 3 N				
Withdrawal force	min. 1.5 N				
Hot plugging	No				
Mechanical Shock IEC 61373 (05/10) 5 g, 30 ms, 5 shocks/axis and each direction no contact disturbance >= 1 µs for p/n ...5xxx					
Random Vibration IEC 61373 (05/10) Cat 1 class B 5.72 m/s ² no contact disturbance >= 1 µs for p/n ...5xxx					
Vibration 10-150 Hz, 0.35mm, 5 g, 2 h each axes -> No contact disturbance >= 1 µs for p/n ...1xxx					
RoHS - compliant	Yes				
UL file	E314677				

Isulator material

Material	PA/PPA	PA/PPA	PA/PPA	PA	PA
Color	black	black	black	green	green
Moisture Sensitivity Level (MSL)	1	1	1	1	1
UL classification	UL 94-V0	UL 94-V0	UL 94-V0	UL 94-V0	UL 94-V0
Material group acc. to IEC 60664-1	I (CTI > 600)	I (CTI > 600)	I (CTI > 600)	I (CTI > 600)	I (CTI > 600)



Contact material

Contact material	Copper alloy
Plating termination zone	Sn
Plating contact zone	Sn


Derating

The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60512-5



Soldering instructions for lead-free tin soldering



25°C (77°F)
from 150°C (302°F) to 190°C (374°F)
from 150s to 180s
1,5°C/s (34°F/s)

from 260°C (500°F) to 275°C (527°F)
from 10s to 30s

Packaging units

types 3.50/3.81 MTV

Type of packaging	No. of poles (xx)	Quantity	Index (xxx)	Remark
box	2	300	000	
box	3	200	000	
box	4 - 5	150	000	
box	6-12	100	000	
box	13 - 20	50	000	
box	21 - 25	25	000	

types 5.00/5.08 MTV

Type of packaging	No. of poles (xx)	Quantity	Index (xxx)	Remark
box	2	300	000	
box	3	200	000	
box	4 - 5	150	000	
box	6 - 12	100	000	
box	13 - 20	50	000	
box	21 - 25	25	000	

types 3.50/5.00/5.08 MWV

Type of packaging	No. of poles (xx)	Quantity	Index (xxx)	Remark
box	2	300	000	
box	3	200	000	
box	4 - 5	150	000	
box	6 - 12	100	000	

1412xx14001xxx

- ¹⁾ (overvoltage cat. II / pollution degree 2)
- ²⁾ (overvoltage cat. III / pollution degree 2)
- ³⁾ (overvoltage cat. III / pollution degree 3)
- ⁴⁾ (overvoltage cat. II / pollution degree 2)
- ⁵⁾ (overvoltage cat. III / pollution degree 2)
- ⁶⁾ (overvoltage cat. III / pollution degree 3)



All Dimensions in mm
Original Size DIN A3

Scale
1:1

Free size tol.

Ref.

Sub.



All rights reserved

Department EL PD

Created by
ZHUANGJ

Inspected by
LUOK

Standardisation
302077

Date
2020-11-23

State
Final Release

Title
har-flexicon male connector, vertical

Doc-Key / ECM-Nr.
100579746/UGD/000/F
500000183169

Type
DS

Number
14121400201

Rev. F Page
1/1

HARTING Electronics GmbH

D-32339 Espelkamp