


ONE CONDUCTOR CABLE, MODIFIED POLYESTER INSULATED, SHIELDED AND ZEROHALOGEN JACKETED, 600 VOLT, 105°C, LIGHTWEIGHT

The complete requirements for procuring the wire described herein shall consist of this document.  
(See below for specification release)



Part Number	Wire Size	Shield Size (mm)	Jacket Thickness (mm)		Overall Diameter (mm)		Maximum Weight (kg/km)
			Min	Nom	Min	Max	
99M1111-26-**-*	26	0.10	0.15	0.20	1.60	2.00	8.29
99M1111-24-**-*	24	0.10	0.15	0.20	1.70	2.10	9.88
99M1111-22-**-*	22	0.10	0.15	0.20	1.85	2.25	12.00
99M1111-20-**-*	20	0.10	0.15	0.20	2.10	2.50	16.00
99M1111-18-**-*	18	0.10	0.15	0.20	2.35	2.75	21.30
99M1111-16-**-*	16	0.10	0.15	0.20	2.75	3.15	29.20
99M1111-14-**-*	14	0.10	0.15	0.20	2.90	3.35	34.80
99M1111-12-**-*	12	0.10	0.15	0.20	3.25	3.70	43.10

**SPECIFICATION RELEASE:** To Def Stan 61-12 (part 18) Issue 4 Type 1, component colours pink or white and black jacket only.  
or  
To Raychem specification WCD 281 and Def Stan 61-12 (part 31), any component colour but black jacket only. (Latest Iss.)  
or  
To Raychem specification WCD 281 and WCD 2015 for any colour selection. (Latest Iss)

**TEMPERATURE RATING:** 105°C for 40,000 hours (by extrapolation)

**COLOUR CODE:** The "\*" in the part number shall be replaced by a standard colour code designator in accordance with Mil Std 681.  
See above for colour/specification selections

eg: 99M1111-24-2-0, core red, jacket black

**W & C DESIGN**  
RED STAMP - CONTROL COPY  
BLACK STAMP - CHECK FOR  
LATEST ISSUE

DESIGN	PROD. MAN.	TECHNICAL	QA	MANUFACTURE
<i>[Signature]</i> 5.6.97	<i>[Signature]</i> 6.6.97	<i>[Signature]</i> 19/6/97	<i>[Signature]</i> 18/6/97	<i>[Signature]</i> 9/6/97

~ Zerohal is a trade mark of Raychem Ltd.

Raychem Limited  
Faraday Road  
Dorcan  
SWINDON  
SN3 5HH  
Tel: (01793)  
528171  
Telex: 449409

Registration Number: 674709 London, England  
Registered Office: Rolls House  
7 Rolls Buildings, Fetter Lane  
LONDON  
EC4A 1NH

This drawing and the information set forth hereon are the property of Raychem Ltd. and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorised in writing by Raychem Ltd. is prohibited.

This specification sheet takes precedence over documents referenced herein. As Raychem Ltd. reserve the right to make changes in construction without notice please contact Raychem Ltd. to ensure that this document is the latest issue.