

APPLICATOR PARTS LIST

TYPE
LENGTHWISE
RING
AMPLIFIER
STUD RETAINING

WITH WIRE AMP INCORPORATED
TRIM HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER	1	456408-6	42	WIRE TRIMMER	1	811264-2	
2	INS. CRIMPER			43				
3	ANVIL	1	473405-9	44				
4	ANVIL SPACER			45	SPACER, GUARD	2	377026	
5	SHEAR BLADE	1	4-465233-1	46				
6	REAR SHEAR PLATE	1	535013-4	47				
7	SHEAR BLADE SPACER	2	373072	48				
8	FRONT SHEAR PLATE	1	810490-1	49				
9	REAR ANVIL SPACER PLT.	1	374769	50				
10	FRONT ANVIL SPACER PLT.	1	370483	51				
11	TOOL SPACER	2	810015	52				
12	CRIMP SPACER			53	HOLD DOWN (BLADE MT.)	1	8110651	
13	FRONT STRIP GUIDE	1	1-472438-9	54				
14	REAR STRIP GUIDE	1	2-472438-0	55				
15	RAM	1	471167	56				
16	TOOL HOLDER	1	376046	57				
17	ADJ. CRIMP MOUNT			58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.	1	570656	60				
20	BASE PLATE			61				
21	BASE BLOCK			62				
22	STRIP GUIDE PLATE			63				
23	ANVIL HOLDER	1	370526	64				
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ. RATE	1	374999	
25	STRIPPER & WIRE TRIMMER	1	811265-1	MISCELLANEOUS				
26	STRIPPER MOUNT	2	386231	66	AIR BLAST ASSY	1	455350-3	
27	RETAINER PLATE	2	572257	67	TUBE, COPPER	1	689446-2	
28	STRIPPER MOUNT BRACKET			68	ELBOW	1	22317-3	
29	STRIPPER BUSHING			69				
30	STOCK DRAG	1	375381	70	LUBRICATOR ASSY.	1	465184-2	
31	STOCK DRAG HANDLE			71	TERMINAL LUBRICANT	1	22014-1	
32	STOCK DRAG STUD	2	354045-1	72				
33	STOCK DRAG SPRING	2	1-23847-1	REV. REVISION RECORD				
34	STOCK DRAG ADJ. SCREW	2	572947	REV.	REVISION RECORD	DATE	BY	ECN
35	FEED FINGER HOLDER			E	0150-6442-95	10/95	lsc	
36	FEED FINGER	1	375093	D	ECN A-395892	9-92	ms	
37	FEED FINGER TIP			C	ECN A-298891	4/91	DS	
38	FEED FINGER SPACER			B	REV. ITEM #45 ECN	1-89	DS	
39	BASE CASTING	1	570238	AI	ADDED TERM. 505076	9/25/76	DS	B3209
40	GUARD	1	457064-2	A	REV PER ECN (70 & 71)	11/10/78	DS	R2752
41				OI	REV. PER ECN	9-12-78	DS	R2684

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				505017 505075
WIRE SIZE	CRIMP HEIGHT			
				WITH LEGS 505072 505076
CRIMP WIRE	SIZE 1110	TYPE F	FEED 1.000	
INSUL. SLEEVED				
WIRE RANGE MAG. WIRE 1000-2600 CMA				
EXPLODED VIEW A-6000 A-6000-1				
REMARKS: REAR STRIP GUIDE MUST BE ADJUSTED TO APPLY DIFFERENT TERMINALS. TOP TOOL MOUNTING ITEM 5, 11, 11, 42 & 1				
THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.				
DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT				
THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3				
MECH. FEED ALIGN. GA. 679597-1				DIST. 4
SERIAL NO.	DATE SHIPPED	DESIGNED		
CUSTOMER NAME AND ADDRESS		CHK'D.	3-78	
APPLICATOR NUMBER		REV. E	566260-2	
SHEET		1 OF 1		