


MSC040SMA120J Silicon Carbide N-Channel Power MOSFET Datasheet

1 Product Overview

This section shows the product overview for the MSC040SMA120J device.



1.1 Features

The following are key features of the MSC040SMA120J device:

- Low capacitances and low gate charge
- Fast switching speed due to low internal gate resistance (ESR)
- Stable operation at high junction temperature, $T_{J(max)} = 175\text{ }^{\circ}\text{C}$
- Fast and reliable body diode
- Superior avalanche ruggedness
- RoHS compliant
- Isolated voltage to 2500 V

1.2 Benefits

The following are benefits of the MSC040SMA120J device:

- High efficiency to enable lighter, more compact system
- Simple to drive and easy to parallel
- Improved thermal capabilities and lower switching losses
- Eliminates the need for external freewheeling diode
- Lower system cost of ownership

1.3 Applications

The MSC040SMA120J device is designed for the following applications:

- PV inverter, converter, and industrial motor drives
- Smart grid transmission and distribution
- Induction heating and welding
- H/EV powertrain and EV charger
- Power supply and distribution

2 Device Specifications

This section shows the specifications for the MSC040SMA120J device.

2.1 Absolute Maximum Ratings

The following table shows the absolute maximum ratings for the MSC040SMA120J device.

Table 1 • Absolute Maximum Ratings

Symbol	Parameter	Ratings	Unit
V_{DSS}	Drain source voltage	1200	V
I_D	Continuous drain current at $T_c = 25\text{ }^\circ\text{C}$	53	A
	Continuous drain current at $T_c = 100\text{ }^\circ\text{C}$	37	
I_{DM}	Pulsed drain current ¹	105	
V_{GS}	Gate-source voltage	25 to -10	V
P_D	Total power dissipation at $T_c = 25\text{ }^\circ\text{C}$	208	W
	Linear derating factor	1.19	W/ $^\circ\text{C}$

Note:

1. Repetitive rating: pulse width and case temperature limited by maximum junction temperature.

The following table shows the thermal and mechanical characteristics for the MSC040SMA120J device.

Table 2 • Thermal and Mechanical Characteristics

Symbol	Characteristic	Min	Typ	Max	Unit
$R_{\theta JC}$	Junction-to-case thermal resistance		0.48	0.72	$^\circ\text{C}/\text{W}$
T_J	Operating junction temperature	-55		175	$^\circ\text{C}$
T_{STG}	Storage temperature	-55		150	
$V_{Isolation}$	RMS voltage (50-60 Hz sinusoidal waveform from terminals to mounting base for 1 minute).	2500			V
	Mounting torque, M4 screw			10	lbf-in
					1.1
W_t	Package weight		1.03		oz
				29.2	g

2.2 Electrical Performance

The following table shows the static characteristics for the MSC040SMA120J device. $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified.

Table 3 • Static Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0\text{ V}, I_D = 100\text{ }\mu\text{A}$	1200			V
$R_{DS(on)}$	Drain-source on resistance ¹	$V_{GS} = 20\text{ V}, I_D = 40\text{ A}$		40	50	m Ω
$V_{GS(th)}$	Gate-source threshold voltage	$V_{GS} = V_{DS}, I_D = 1\text{ mA}$	1.8	2.8		V

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$\Delta V_{GS(th)}/\Delta T_J$	Threshold voltage coefficient (see Figure 11)	$V_{GS} = V_{DS}, I_D = 1 \text{ mA}$		-4.5		mV/°C
I_{DSS}	Zero gate voltage drain current	$V_{DS} = 1200 \text{ V}, V_{GS} = 0 \text{ V}$ $V_{DS} = 1200 \text{ V}, T_J = 125 \text{ }^\circ\text{C},$ $V_{GS} = 0 \text{ V}$			100 500	μA
I_{GSS}	Gate-source leakage current	$V_{GS} = 20 \text{ V}/-10 \text{ V}$			± 100	nA

Note:

1. Pulse test: pulse width < 380 μs , duty cycle < 2%.

The following table shows the dynamic characteristics for the MSC040SMA120J device. $T_J = 25 \text{ }^\circ\text{C}$ unless otherwise specified.

Table 4 • Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input capacitance	$V_{GS} = 0 \text{ V}, V_{DD} = 1000 \text{ V}, V_{AC} = 25 \text{ mV},$ $f = 1 \text{ MHz}$		1990		μF
C_{rSS}	Reverse transfer capacitance			17		
C_{oss}	Output capacitance			156		
Q_g	Total gate charge	$V_{GS} = -5 \text{ V}/20 \text{ V}, V_{DD} = 800 \text{ V}, I_D = 40 \text{ A}$		137		nC
Q_{gs}	Gate-source charge			29		
Q_{gd}	Gate-drain charge			31		
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 800 \text{ V}, V_{GS} = 0 \text{ V}/20 \text{ V}, I_D = 40 \text{ A},$ $R_{G(ext)} = 5.3 \text{ } \Omega^1, \text{ Freewheeling diode} =$ MSC015SDA120B		10		ns
t_r	Current rise time			10		
$t_{d(off)}$	Turn-off delay time			55		
t_f	Current fall time			25		
E_{on2}	Turn-on switching energy ²			930		μJ
E_{off}	Turn-off switching energy			585		
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 800 \text{ V}, V_{GS} = 0 \text{ V}/20 \text{ V}, I_D = 40 \text{ A},$ $R_{G(ext)} = 5.3 \text{ } \Omega^1, T_c = 150 \text{ }^\circ\text{C},$ $\text{Freewheeling diode} = \text{MSC015SDA120B}$		10		ns
t_r	Current rise time			10		
$t_{d(off)}$	Turn-off delay time			74		
t_f	Current fall time			37		
E_{on2}	Turn-on switching energy ²			890		μJ
E_{off}	Turn-off switching energy			855		
ESR	Equivalent series resistance	$f = 1 \text{ MHz}, 25 \text{ mV}, \text{ drain short}$		1.2		Ω
SCWT	Short circuit withstand time	$V_{DS} = 960 \text{ V}, V_{GS} = 20 \text{ V}, T_c = 25 \text{ }^\circ\text{C}$		3		μs
E_{AS}	Avalanche energy, single pulse	$V_{DS} = 150 \text{ V}, V_{GS} = 20 \text{ V}, I_D = 40 \text{ A},$ $T_c = 25 \text{ }^\circ\text{C}, I_L = 2.5\text{mH}$		2000		mJ

Notes:

1. R_G is total gate resistance excluding internal gate driver impedance.
2. E_{on2} includes energy of MSC015SDA120B freewheeling diode.

The following table shows the body diode characteristics for the MSC040SMA120J device. $T_J = 25 \text{ }^\circ\text{C}$ unless otherwise specified.

Table 5 • Body Diode Characteristics

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{SD}	Diode forward voltage	$I_{SD} = 40\text{ A}, V_{GS} = 0\text{ V}$		3.9		V
		$I_{SD} = 40\text{ A}, V_{GS} = -5\text{ V}$		4.1		V
t_{rr}	Reverse recovery time	$I_{SD} = 40\text{ A}, V_{GS} = -5\text{ V},$ $V_{DD} = 800\text{ V}, dl/dt = -1000\text{ A}/\mu\text{s}$		100		ns
Q_{rr}	Reverse recovery charge			550		nC
I_{RRM}	Reverse recovery current			12.5		A

2.3 Typical Performance Curves

This section shows the typical performance curves for the MSC040SMA120J device.

Figure 1 • Drain Current vs. Drain-to-Source Voltage




Figure 2 • Drain Current vs. Drain-to-Source Voltage




Figure 3 • Drain Current vs. Drain-to-Source Voltage




Figure 4 • Drain Current vs. Drain-to-Source Voltage




Figure 5 • RDS(on) vs. Junction Temperature




Figure 6 • Gate Charge Characteristics




Figure 7 • Capacitance vs. Drain-to-Source Voltage




Figure 8 • IDM vs. Gate-to-Source Voltage




Figure 9 • IDM vs. VDS Third Quadrant Conduction




Figure 10 • IDM vs. VDS Third Quadrant Conduction




Figure 11 • VGS(th) vs. Junction Temperature




Figure 12 • Forward Safe Operating Area





Figure 13 • Maximum Transient Thermal Impedance




3 Package Specification

This section shows the package specification for the MSC040SMA120J device.

3.1 Package Outline Drawing

This section shows the SOT-227 package drawing for the MSC040SMA120J device. The dimensions in the figure below are in millimeters and (inches).

Figure 14 • Package Outline Drawing





Microsemi Headquarters

One Enterprise, Aliso Viejo,
CA 92656 USA

Within the USA: +1 (800) 713-4113

Outside the USA: +1 (949) 380-6100

Sales: +1 (949) 380-6136

Fax: +1 (949) 215-4996

Email: sales.support@microsemi.com

www.microsemi.com

© 2019 Microsemi. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

Microsemi, a wholly owned subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California, and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

050-7738 | April 2019 | Preliminary