



### **LUMILEDS LUXEON C Starboards**

# **Data Sheet**

Industry Leading High Powered LED Starboards

Version 1.0

#### Lean & Fast, Made Smarter.

**Superior Performance** – Stay current with the highest intensity LEDs

**Design Faster** - Use industry standard starboards to shorten development time

**Maximum Flexibility** - Design to your exact specifications using the full spectrum of NewEnergy starboards

**Rapid Innovation** – Work with NewEnergy on your custom solution

#### **Primary Applications**









Architectural
Emergency Vehicle
Downlight
Stage/concert
Spot lighting
Floodlight

#### **Superior Performance with Flexible Options**

- · Multiple color options for your application
- · Single focal length for all colors to ensure superior mixing
- · Small source size reduces the size of secondary optics
- · Prototype faster, test multiple options

#### **Custom Solutions**

NewEnergy operates facilities globally with ISO certifications for the LED lighting, automotive and medical industries. Our North Carolina based office provides quick engineering & sales support with an R&D lab for prototype development and custom solutions. Our in-house global manufacturing capabilities allow for both building in the United States as well as overseas at scale.



#### About NewEnergy

NewEnergy accelerates the adoption of LED technology through simple, modular products and custom designs. Through 30 years of experience, state of the art manufacturing, full traceability and advanced quality controls, NewEnergy offers leading solid state lighting components, modules and custom solutions. NewEnergy customers get to market faster, with less resources, at lower costs. Visit new-energyllc.com for more information.



RoHS ( E

# **LUMILEDS LUXEON C Starboards**

## Product Selection Guide

Part Number	CRI/Color	CCT/ Typical Peak Wavelength Range	Typical Viewing Angle	Typical Luminous Flux (mW)	Typical Forward Voltage (Vf)	Typical Wattage (W)
LST1-01H06-RED1-01	Red	624-634	162°	49	2.00	0.70
LST1-01H06-PCA1-01	Amber	n/a <sup>(2)</sup>	162°	94	2.75	0.96
LST1-01H06-LME1-01	Lime	n/a <sup>(2)</sup>	145°	135	2.75	0.96
LST1-01H06-GRN1-01	Green	520-540	170°	141	3.05	1.07
LST1-01H06-BLU1-01	Blue	465-485	170°	43	2.84	0.99
LST1-01H06-VLT1-01	Violet	420-430	165°	595	2.83	0.99
LST1-01H06-3080-01	80	3000K	150°	102	2.75	0.96
LST1-01H06-4080-01	80	4000K	150°	113	2.75	0.96


 $<sup>^{(1)}</sup>$ Flux, wavelength, and wattage values specified at 350mA,  $T_{_{\rm i}}$  85°C


Additional colors available upon request.

## Maximum Ratings

Part Number	DC Current (A)	Tsp Temp (°C)	Power (W)
LST1-01H06-RED1-01	1.05	105	2.6
LST1-01H06-PCA1-01	1.05	105	3.7
LST1-01H06-LME1-01	1.23	105	4.3
LST1-01H06-GRN1-01	1.05	105	3.7
LST1-01H06-BLU1-01	1.05	105	3.7
LST1-01H06-VLT1-01	1.23	105	4.3
LST1-01H06-x080-01	1.23	105	4.3

### Mechanical Dimensions (Units: Inches)







<sup>&</sup>lt;sup>(2)</sup>Amber and Lime starboards are binned by chromaticity coordinates, see LUMILEDS LED datasheet for values.

All values shown above are typical.