

Ratings

Voltage: 600 V
 Temperature: -40~105 °C
 Flammability: VW-1

Conductor

Conductor count: 1
 Gauge: 26 AWG 0.13 mm²
 Material: tinned copper strands
 Strand size: Ø 0.08 mm x 26
 Resistance at 20 °C: 150 Ω /km max


Insulator

Material: Polyphenylene Ether, Modified (mPPE)
 Color: gray
 Diameter: Ø 1 ±0.10 mm
 Nominal thickness: 0.25 mm
 Resistance at 20 °C: 100 MΩ /km min

Wire marking: E339579 UL AWM STYLE 11028 26 AWG 105°C
 600V VW-1 --- cUL AWM I A/B 105°C 600V FT1 TENSILITY

Bend radius

Minimum: 4 times diameter (4.0 mm)



Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com	
A	3/2/2021	Initial release	AG <small>Digitally signed by AG Date: 2021.03.02 14:39:31 -08'00'</small>			RoHS compliant
			Verified:	Phthalate and halogen free	Description: Wire, hook-up, TS, 26 AWG, UL 11028, 600V, 105C, 1 mm, mPPE, gray	
			AW <small>Digitally signed by AW Date: 2021.03.05 12:05:12 -08'00'</small>			
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	Size:	Part number:
					A	30-01780
					Scale: 30:1	Sheet 1 of 1

5

4

3

2

1