



Main

Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Number of terminals	6
Switch function	DPST
Contacts type and composition	2 NO

Complementary

[In] rated current	30 A
[Ue] rated operational voltage	300 V
Connections - terminals	Screw terminal, clamping connection capacity: 6 mm ² , AWG 10 solid screw terminal, clamping connection capacity: 2 x 0.5...2 x 6 mm ² , AWG 20...AWG 10 stranded
Tightening torque	Screw: 1.2 N.m
Fixing mode	Clip-on, for 35 mm symmetrical DIN rail
Net weight	67 G
Depth	70.5 Mm

Environment

Flame retardance	UL94-V0
------------------	---------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.08 Cm
Package 1 Width	5.4 Cm
Package 1 Length	2.35 Cm
Package 1 Weight	67 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.6 Cm
Package 2 Width	11.1 Cm
Package 2 Length	12.4 Cm
Package 2 Weight	670 G
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Height	27.5 Cm
Package 3 Width	23.7 Cm

Package 3 Length	40.5 Cm
Package 3 Weight	13.4 Kg

Product Life Status : **Commercialised**