

Description

The DGD2184M is a high-voltage and high-speed gate driver capable of driving N-Channel MOSFETs and IGBTs in a half bridge configuration. High-voltage processing techniques enable the DGD2184M's high-side to switch to 600V in a bootstrap operation.

The DGD2184M logic inputs are compatible with standard TTL and CMOS levels (down to 3.3V) for easy interfacing with controlling devices. The driver outputs feature high-pulse current buffers designed for minimum driver cross conduction. The DGD2184M has a fixed internal deadtime of 395ns (typ).

The DGD2184M is offered in the SO-8 (Type TH) package, and the operating temperature extends from -40°C to +125°C.

Applications

- DC-DC converters
- DC-AC inverters
- AC-DC power supplies
- Motor controls
- Class D power amplifiers


Features

- Floating High-Side Driver in Bootstrap Operation to 600V
- Drives Two N-Channel MOSFETs or IGBTs in Half Bridge Configuration
- 1.9A Source / 2.3A Sink Output Current Capability
- Outputs Tolerant to Negative Transients
- Internal Dead Time of 395ns to Protect MOSFETs
- Wide Low-Side Gate Driver and Logic Supply: 10V to 20V
- Logic Input (IN and SD*) 3.3V Capability
- Schmitt Triggered Logic Inputs with Internal Pull Down
- Undervoltage Lockout for High- and Low-Side Drivers
- Extended Temperature Range: -40°C to +125°C
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please [contact us](#) or your local Diodes representative.**

<https://www.diodes.com/quality/product-definitions/>

Mechanical Data

- Package: SO-8 (Type TH)
- Package Material: Molded Plastic. "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminals: Finish – Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 (E3)
- Weight: 0.075 grams (Approximate)



Typical Configuration




Top View

Ordering Information (Note 4)

| Orderable Part Number | Package | Marking | Reel Size (inch) | Tape Width (mm) | Packing | |
|-----------------------|----------------|----------|------------------|-----------------|---------|---------|
| | | | | | Qty. | Carrier |
| DGD2184MS8-13 | SO-8 (Type TH) | DGD2184M | 13 | 12 | 2,500 | Reel |


- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
 2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 4. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.

Marking Information



⌋⌋ = Manufacturer's Marking
 DGD2184M = Product Type Marking Code
 YY = Year (ex: 23 = 2023)
 WW = Week (01 to 53)

Pin Diagrams




Top View SO-8

Pin Descriptions

| Pin Number | Pin Name | Function |
|------------|-----------------|--|
| 1 | IN | Logic Input for High-Side and Low-Side Gate Driver Outputs (HO and LO), in Phase with HO |
| 2 | SD* | Logic Input for Shutdown, Enabled Low |
| 3 | COM | Low-Side and Logic Return |
| 4 | LO | Low-Side Gate Drive Output |
| 5 | V _{CC} | Low-Side and Logic Fixed Supply |
| 6 | V _S | High-Side Floating Supply Return |
| 7 | HO | High-Side Gate Drive Output |
| 8 | V _B | High-Side Floating Supply |

Functional Block Diagram



Absolute Maximum Ratings (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|--|-------------|----------------------------|------|
| High-Side Floating Supply Voltage | V_B | -0.3 to +624 | V |
| High-Side Floating Supply Offset Voltage | V_S | $V_B - 24$ to $V_B + 0.3$ | V |
| High-Side Floating Output Voltage | V_{HO} | $V_S - 0.3$ to $V_B + 0.3$ | V |
| Offset Supply Voltage Transient | dV_S / dt | 50 | V/ns |
| Low-Side Fixed Supply Voltage | V_{CC} | -0.3 to +24 | V |
| Low-Side Output Voltage | V_{LO} | -0.3 to $V_{CC} + 0.3$ | V |
| Logic Input Voltage (IN and SD*) | V_{IN} | -0.3 to $V_{CC} + 0.3$ | V |

Thermal Characteristics (@ $T_A = +25^\circ\text{C}$, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|---|-----------------|-------------|---------------------------|
| Power Dissipation Linear Derating Factor (Note 5) | P_D | 0.625 | W |
| Thermal Resistance, Junction to Ambient (Note 5) | $R_{\theta JA}$ | 200 | $^\circ\text{C}/\text{W}$ |
| Operating Temperature | T_J | +150 | $^\circ\text{C}$ |
| Lead Temperature (Soldering, 10s) | T_L | +300 | |
| Storage Temperature Range | T_{STG} | -55 to +150 | |

Note: 5. When mounted on a standard JEDEC 2-layer FR-4 board.

Recommended Operating Conditions

| Parameter | Symbol | Min | Max | Unit |
|--|----------|------------|------------|------------------|
| High-Side Floating Supply Absolute Voltage | V_B | $V_S + 10$ | $V_S + 20$ | V |
| High-Side Floating Supply Offset Voltage | V_S | (Note 6) | 600 | V |
| High-Side Floating Output Voltage | V_{HO} | V_S | V_B | V |
| Low-Side Fixed Supply Voltage | V_{CC} | 10 | 20 | V |
| Low-Side Output Voltage | V_{LO} | 0 | V_{CC} | V |
| Logic Input Voltage (IN and SD*) | V_{IN} | 0 | V_{CC} | V |
| Ambient Temperature | T_A | -40 | +125 | $^\circ\text{C}$ |

Note: 6. Logic operation for V_S of -5V to +600V.

DC Electrical Characteristics (V_{BIAS} (V_{CC} , V_{BS}) = 15V, @ T_A = +25°C, unless otherwise specified.) (Note 7)

| Parameter | Symbol | Min | Typ | Max | Unit | Conditions |
|--|-------------|-----|-----|-----|---------|---------------------------------|
| Logic "1" Input Voltage | V_{IH} | 2.5 | — | — | V | $V_{CC} = 10V$ to 20V |
| Logic "0" Input Voltage | V_{IL} | — | — | 0.8 | V | $V_{CC} = 10V$ to 20V |
| SD* Input Positive Going Threshold | V_{SDTH+} | 2.5 | — | — | V | $V_{CC} = 10V$ to 20V |
| SD* Input Negative Going Threshold | V_{SDTH-} | — | — | 0.8 | V | $V_{CC} = 10V$ to 20V |
| High Level Output Voltage, $V_{BIAS} - V_O$ | V_{OH} | — | — | 1.2 | V | $I_O = 0mA$ |
| Low Level Output Voltage, V_O | V_{OL} | — | — | 0.1 | V | $I_O = 20mA$ |
| Offset Supply Leakage Current | I_{LK} | — | — | 50 | μA | $V_B = V_S = 600V$ |
| Quiescent V_{BS} Supply Current | I_{BSQ} | 20 | 60 | 150 | μA | $V_{IN} = 0V$ or 5V |
| Quiescent V_{CC} Supply Current | I_{CCQ} | 0.4 | 1.0 | 1.8 | mA | $V_{IN} = 0V$ or 5V |
| Logic "1" Input Bias Current | I_{IN+} | — | 25 | 60 | μA | $I_N = 5V$, $SD^* = 0V$ |
| Logic "0" Input Bias Current | I_{IN-} | — | — | 1.0 | μA | $I_N = 0V$, $SD^* = 5V$ |
| V_{BS} Supply Under-Voltage Positive Going Threshold | V_{BSUV+} | 8.0 | 8.9 | 9.8 | V | — |
| V_{BS} Supply Under-Voltage Negative Going Threshold | V_{BSUV-} | 7.4 | 8.2 | 9.0 | V | — |
| V_{CC} Supply Under-Voltage Positive Going Threshold | V_{CCUV+} | 8.0 | 8.9 | 9.8 | V | — |
| V_{CC} Supply Under-Voltage Negative Going Threshold | V_{CCUV-} | 7.4 | 8.2 | 9.0 | V | — |
| Output High Short Circuit Pulsed Current | I_{O+} | 1.4 | 1.9 | — | A | $V_O = 0V$, $PW \leq 10\mu s$ |
| Output Low Short Circuit Pulsed Current | I_{O-} | 1.7 | 2.3 | — | A | $V_O = 15V$, $PW \leq 10\mu s$ |

Note: 7. The V_{IN} and I_{IN} parameters are applicable to the two logic input pins: I_N and SD^* . The V_O and I_O parameters are applicable to the respective output pins: HO and LO.

AC Electrical Characteristics (V_{BIAS} (V_{CC} , V_{BS}) = 15V, $C_L = 1000pF$, @ T_A = +25°C, unless otherwise specified.)

| Parameter | Symbol | Min | Typ | Max | Unit | Conditions |
|---|-------------|-----|-----|-----|------|--------------------|
| Turn-On Propagation Delay | t_{on} | — | 585 | 900 | ns | $V_S = 0V$ |
| Turn-Off Propagation Delay | t_{off} | — | 170 | 400 | ns | $V_S = 0V$ or 600V |
| Shut-Down Propagation Delay | t_{SD} | — | 180 | 270 | ns | — |
| Delay Matching, HO & LO Turn-On | t_{DMON} | — | — | 90 | ns | — |
| Delay Matching, HO & LO Turn-Off | t_{DMOFF} | — | — | 40 | ns | $I_O = 0A$ |
| Turn-On Rise Time | t_r | — | 40 | 60 | ns | $V_S = 0V$ |
| Turn-Off Fall Time | t_f | — | 20 | 35 | ns | $V_S = 0V$ |
| Deadtime: $t_{DT LO-HO}$ & $t_{DT HO-LO}$ | t_{DT} | 345 | 395 | 445 | ns | — |

Timing Waveforms




Figure 1. Input / Output Timing Diagram





Figure 2. Shutdown Waveform Definitions



$Deadtime\ t_{DT\ LO-HO} = t_{ON\ HO} - t_{OFF\ LO}$
 $t_{DT\ HO-LO} = t_{ON\ LO} - t_{OFF\ HO}$
 Deadtime matching
 $t_{MDT} = t_{DT\ LO-HO} - t_{DT\ HO-LO}$

Delay matching
 $t_{DM\ OFF} = t_{OFF\ LO} - t_{OFF\ HO}$

Figure 3. Switching Time Waveform Definitions

Typical Performance Characteristics (@T_A = +25°C, V_{CC} = 15V, unless otherwise specified.)




Figure 4. Turn-on Propagation Delay vs. Supply Voltage




Figure 5. Turn-on Propagation Delay vs. Temperature




Figure 6. Turn-off Propagation Delay vs. Supply Voltage




Figure 7. Turn-off Propagation Delay vs. Temperature




Figure 8. Rise Time vs. Supply Voltage




Figure 9. Rise Time vs. Temperature

Typical Performance Characteristics (continued)




Figure 10. Fall Time vs. Supply Voltage




Figure 11. Fall Time vs. Temperature




Figure 12. Quiescent Current vs. Supply Voltage




Figure 13. Quiescent Current vs. Temperature




Figure 14. Delay Matching vs. Supply Voltage




Figure 15. Delay Matching vs. Temperature

Typical Performance Characteristics (continued)




Figure 16. Output Source Current vs. Supply Voltage




Figure 17. Output Source Current vs. Temperature




Figure 18. Output Sink Current vs. Supply Voltage




Figure 19. Output Sink Current vs. Temperature




Figure 20. Logic 1 Input Voltage vs. Supply Voltage




Figure 21. Logic 1 Input Voltage vs. Temperature

Typical Performance Characteristics (continued)




Figure 22. Logic 0 Input Voltage vs. Supply Voltage




Figure 23. Logic 0 Input Voltage vs. Temperature




Figure 24. Deadtime vs. Supply Voltage




Figure 25. Deadtime vs. Temperature




Figure 26. VCC UVLO vs. Temperature




Figure 27. VBS UVLO vs. Temperature

Typical Performance Characteristics (continued)





Figure 28. Offset Supply Leakage Current vs. Temperature

Package Outline Dimensions

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SO-8 (Type TH)




| SO-8 (Type TH) | | | |
|-----------------------------|---------|-------|------|
| Dim | Min | Max | Typ |
| A | -- | 1.75 | -- |
| A1 | 0.10 | 0.225 | -- |
| A2 | 1.30 | 1.50 | 1.40 |
| A3 | 0.60 | 0.70 | 0.65 |
| b | 0.39 | 0.47 | -- |
| c | 0.20 | 0.24 | -- |
| D | 4.80 | 5.00 | 4.90 |
| E | 5.80 | 6.20 | 6.00 |
| E1 | 3.80 | 4.00 | 3.90 |
| e | 1.27BSC | | |
| h | 0.25 | 0.50 | -- |
| L | 0.50 | 0.80 | -- |
| L1 | 1.05REF | | |
| a | 0° | 8° | -- |
| All Dimensions in mm | | | |

Suggested Pad Layout

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

SO-8 (Type TH)



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 1.27 |
| C1 | 5.20 |
| X | 0.60 |
| Y | 2.20 |

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.
4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.
5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (<https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/>) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.
9. This Notice may be periodically updated with the most recent version available at <https://www.diodes.com/about/company/terms-and-conditions/important-notice>

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2023 Diodes Incorporated. All Rights Reserved.

www.diodes.com