

Product data sheet

Specifications



set of 2 Spacial SF lifting bar - zinc coated - 1600 mm

NSYSFTB16

Main

Bereich	Spacial
Kategorie	Lifting accessory
Product or component type	Lifting bar
Anwendung	Multi-purpose
Mounting location	Enclosure top
Mounting support	Directly in the axis of the uprights
Range compatibility	Spacial (Spacial SF) Spacial (Spacial SFHD) Spacial (Spacial SFM)
Device composition	2 lifting bars fixing elements
Quantity per set	Set of 1

Complementary

Material	Steel
Surface finish	Zinc coated
Fixing mode	By screws - screw type M12
Permanent permissible load	2000 kg
Length	Nominal: 1600 mm Real: 1595 mm
Height	60 mm
Depth	60 mm
Diameter	32 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	12.0 cm
Package 1 Length	209.0 cm
Package 1 Weight	27.1 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)