
## **REVISION B**


DO NOT SCALE FROM THIS PRINT





## **DESIGNED & DIMENSIONED** IN MILLIMETERS[INCHES]

TABLE 1		
ITEM	COMPONENT	-H
1	SUB ASSEMBLY	SUB-SMA-P-C-F-ST-CS5
2	PIN	SMA-PIN-007-H
3	INSULATOR	SMA-INS-018









## NOTES:

- 1. © REPRESENTS A CRITICAL DIMENSION.

- 4. PRODUCT TO BE PACKAGED PER PACKAGING STANDARD CO-RF-WI-3040-M.
- 5. NOTE DELETED.
- 6. NOTE DELETED. 7. NOTE DELETED.

2. CENTER CONTACT PUSHOUT FORCE: 26.69 N [6 LB] MIN. 3. NOTE DELETED.

DO NOT SCALE DRAWING CABLE BODY, COUPLING NUT, C-RING: BRASS

ANGLES

5°

CONTACT: BRASS DIELECTRIC: PTFE GASKET: SILICONE

UNLESS OTHERWISE SPECIFIED,

MILLIMETERS [INCHES].

.X: ±0.3 [.01] .XX: ±0.13 [.005]

.XXX: ±0.051 [.0020]

DECIMALS

TOLERANCES ARE:

## PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR LISED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

DESCRIPTION

SMA STRAIGHT CABLE PLUG, 25 AWG CABLE - 50 OHM

FAX: 812-948-5047

DWG. NO.

SMA-P-C-X-ST-CS5

e-Mail info@SAMTEC.com code 55322

BY: J. BROWNING 06/14/2010

PHONE: 812-944-6733

SHEET 1 OF 2

C:\EnterpriseVault\DWG\MISC\MKTG\SMA-P-C-X-ST-CS5-MKT.SLDDRW

