## ATGBICS CWDM-SFP-2.5G-1530-80 Cisco Compatible Transceiver CWDM SFP 2.5G (80km, SMF, LC, 1530nm)

**Brand:** ATGBICS

**Product code:** CWDM-SFP-2.5G-1530-80-C



**Product name :** CWDM-SFP-2.5G-1530-80 Cisco Compatible Transceiver CWDM SFP 2.5G (80km, SMF, LC,

1530nm)

CWDM-SFP-2.5G-1530-80 Cisco Compatible Transceiver CWDM SFP 2.5G (80km, SMF, LC, 1530nm)

 $\label{thm:condition} \mbox{ATGBICS CWDM-SFP-2.5G-1530-80 Cisco Compatible Transceiver CWDM SFP 2.5G (80km, SMF, LC, 1530nm):}$ 

ATGBICS CWDM-SFP-2.5G-1530-80 2.5GBase CWDM supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1530nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoCWDM-SFP-2.5G-1530-80= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 2500 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Wavelength  Coarse Wavelength Division Multiplexing (CWDM)  Ethernet LAN  Ethernet interface type  Digital Diagnostics Monitoring (DDM)  Figure Piber optic  CSFP  CVDM  WAVELED  SFP  SFP  SFP  SFP  SFP  SFP  SFP  SF	2500 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	✓ × LC	Input voltage Maximum voltage Power consumption (typical) Operational conditions	3.3 V 3.5 V 1 W
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%	
Features	uct colour Silver sing material Metal	Depth Height Weight	56.5 mm 8.5 mm 15 g
Product colour Housing material			
Plug and Play  Hot-swap  Easy to install  Country of origin  Brand compatibility  V  Cisco		Packaging data	
	<b>*</b>	Number of products included Package type	1 pc(s) Box
	•	Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	<b>√</b> RoHS Lead



5056468714671

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.