









ATP Industrial Grade DRAM Modules

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications

Product	Category	Speed (MT/s)	Form Factor	Features
DDR4 	RDIMM RDIMM VLP UDIMM/UDIMM ECC SO-DIMM ECC	2133	<ul style="list-style-type: none"> Low profile Very Low Profile (VLP) options (VLP: 0.74" height) 	<ul style="list-style-type: none"> Density: 4GB to 16GB Increase performance and bandwidth which is up to 3200 MT/s Decrease voltage for better power consumption Provide better reliability, availability and serviceability (RAS) and improve data integrity as well.
DDR3 	LRDIMM RDIMM UDIMM/UDIMM ECC SO-RDIMM SO-DIMM/SO-DIMM ECC mini-RDIMM mini-UDIMM ECC	1866 1600 1333 1066	<ul style="list-style-type: none"> Low profile Very Low Profile (VLP) options (VLP: 0.74" height) Ultra Low Profile (ULP) options (ULP: 0.7"~0.72" height) 	<ul style="list-style-type: none"> Density: 1GB to 32GB 32GB to 64GB(LRDIMM) Chipkill support Fly-by command/address/control bus with on-DIMM termination. Higher bandwidth performance, effectively up to 1866 MT/s Better performance at low power; 1.5V (Normal) and 1.35V(Low Voltage)
DDR2 	RDIMM UDIMM/UDIMM ECC SO-RDIMM SO-CDIMM SO-DIMM mini-RDIMM FB-UDIMM*	800 667 533 400	<ul style="list-style-type: none"> Low Profile Very Low Profile (VLP) options (VLP:0.72"~0.74" height) 	<ul style="list-style-type: none"> Density: 1GB to 8GB Chipkill support FB-DIMM <ul style="list-style-type: none"> Low power and low voltage options Apple FB-DIMM
DDR* 	UDIMM/UDIMM ECC SO-CDIMM SO-DIMM	400 333 266	<ul style="list-style-type: none"> Low Profile Very Low Profile (VLP) options (VLP:0.72"~0.74" height) 	<ul style="list-style-type: none"> Density: 512MB to 1GB Chipkill support
SDRAM* 	RDIMM UDIMM/UDIMM ECC SO-UDIMM	PC 133 PC 100	<ul style="list-style-type: none"> Low Profile Very Low Profile (VLP) options (VLP:0.72"~0.74" height) 	<ul style="list-style-type: none"> Density: 256MB to 1GB Chipkill support Legacy system support

Product Portfolio	Category	Product	Features
Industrial Grade Family 	SO-DIMM UDIMM RDIMM	DDR3 DDR2 DDR* SDRAM*	<ul style="list-style-type: none"> Extended temperature: -40°C ~ +85°C Controlled BOM and SPD For mission critical industrial applications conformal coating

* Available on a project basis.

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6206-8097
FAX: +81-3-6206-8098
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-5080-2219
sales@cn.atpinc.com