

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| COUNT | DESCRIPTION OF REVISIONS | BY  | CHKD | DATE     | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|-------|--------------------------|-----|------|----------|-------|--------------------------|----|------|------|
| △ 2   | RE-F-09653               | K.N | H.Y  | 04.04.06 | △     |                          |    |      |      |
| △ 1   | RE-F-10251               | K.D | H.O  | 05.02.02 | △     |                          |    |      |      |

  

|                             |                 |                           |                 |
|-----------------------------|-----------------|---------------------------|-----------------|
| APPLICABLE STANDARD         |                 |                           |                 |
| OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C |
| RATING VOLTAGE              | 100 V AC        | OPERATING HUMIDITY RANGE  | 40 % TO 80 %    |
| CURRENT                     | 0.4 A           | STORAGE HUMIDITY RANGE    | 40 % TO 70 %    |

  

| ITEM                                      |   | TEST METHOD   | REQUIREMENTS               | QT | AT |
|---|---|---|----------------------------|----|----|
| CONSTRUCTION                              |   |   |                            |    |    |
| GENERAL EXAMINATION                       |   | VISUALLY AND BY MEASURING INSTRUMENT.   | ACCORDING TO DRAWING.      | ×  | ×  |
| MARKING                                   |   | CONFIRMED VISUALLY.   |                            | ×  | ×  |
| ELECTRIC CHARACTERISTICS                  |   |   |                            |    |    |
| CONTACT RESISTANCE                        | 100 mA (DC OR 1000 Hz).   |   | 80 mΩ MAX. (1)             | ×  |    |
| CONTACT RESISTANCE MILLIVOLT LEVEL METHOD | 20 mV MAX. 1 mA(DC OR 1000Hz)   |   | 100 mΩ MAX. (2)            | ×  |    |
| INSULATION RESISTANCE                     | 250 V DC.   |   | 100 MΩ MIN.                | ×  |    |
| VOLTAGE PROOF                             | 300 V AC FOR 1 min.   |   | NO FLASHOVER OR BREAKDOWN. | ×  |    |
| MECHANICAL CHARACTERISTICS                |   |   |                            |    |    |
| MECHANICAL OPERATION                      |   | 50 TIMES INSERTIONS AND EXTRACTIONS.  |                            | ×  |    |
| VIBRATION                                 |   | FREQUENCY 10 TO 55 Hz.<br>AMPLITUDE : 1.5 mm,<br>AT 2 h FOR 3 DIRECTION.  |                            | ×  |    |
| SHOCK                                     |   | 490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms<br>AT 3 TIMES FOR 3 DIRECTIONS.  |                            | ×  |    |
| ENVIRONMENTAL CHARACTERISTICS             |   |   |                            |    |    |
| DAMP HEAT (STEADY STATE)                  | EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.  | ① CONTACT RESISTANCE: 100 mΩ MAX. (2)<br>② INSULATION RESISTANCE: 100 MΩ MIN.<br>③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. |                            | ×  |    |
| RAPID CHANGE OF TEMPERATURE               | TEMPERATURE: 55→+15~+35→+85→+15~+35°C<br>TIME 30 → 2~3 → 30 → 2~3 min<br>UNDER 5 CYCLES.                  | ① CONTACT RESISTANCE: 100 mΩ MAX. (2)<br>② NO HEAVY CORROSION.  |                            | ×  |    |
| CORROSION SALT MIST                       | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.   | ① CONTACT RESISTANCE: 100 mΩ MAX. (2)<br>② NO HEAVY CORROSION.  |                            | ×  |    |
| HYDROGEN SULPHIDE                         | EXPOSED IN 3 PPM FOR 96 h.<br>(TEST STANDARD: JEIDA-38)   | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.   |                            | ×  |    |
| RESISTANCE TO SOLDERING HEAT              | 1) REFLOW SOLDERING: 250 °C MAX.,<br>: 220 °C MIN,<br>FOR 60 s<br>2) SOLDERING IRONS : 360 °C,<br>FOR 5 s | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED.                               |                            | ×  |    |
| SOLDERABILITY                             | △ SOLDERED AT SOLDER TEMPERATURE, 240 ± 3°C,<br>FOR IMMERSION DURATION, 3 s.                              |   |                            | ×  |    |

  

|  |          |            |          |             |          |
|--|----------|------------|----------|-------------|----------|
| REMARKS (1) THIS CONNECTOR'S INITIAL CONTACT RESISTANCE SHALL BE 80 mΩ, BECAUSE OF THE BULK RESISTANCE OF STACKING HEIGHT 16 mm TYPE. (2) AFTER TEST, THE CHANCE OF THE CONTACT RESISTANCE SHALL BE 20 mΩ MAX. |          |            |          |             |          |
| Unless otherwise specified, refer to JIS C 5402.   |          |            |          |             |          |
| Note QT: Qualification Test AT: Assurance Test X: Applicable Test  |          |            |          |             |          |
| REMARKS  | DRAWN    | DESIGNED   | CHECKED  | APPROVED    | RELEASED |
|  | S.SUZUKI | K.NAKAMURA | H.OKAWA  | Y.YOSHIMURA |          |
|  | 03.02.13 | 03.02.13   | 03.02.14 | 03.02.15    |          |

  

|               |                |          |                  |
|---------------|----------------|----------|------------------|
| CODE NO.(OLD) | DRAWING NO.    | CODE NO. | PART NO.         |
| CL            | ELC4-151088-22 |          | FX8C-※※P-SV2(92) |

  

|    |     |   |
|----|-----|---|
| TO | PCK | 1 |
|    |     | 1 |