

Ŧ	G	П	m	O







LAYOUT SHOWN AS

Keying Shown as example

## CHARACTERISTICS

-Mass

BASIC SERIES:

SHELL SIZE : 13

PLATING : S = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ယ

-Standard : Based on MIL-DTL-38999 Series III

	-Shell Material	: Stainless Steel			
	-Shell Plating	: Nickel			
	-Insulator	: Thermoplastic			
	-Contacts	: Copper Alloy			
	-Seals & Grommet	: Silicon Elastomer			
N	-Contact Plating	: Gold over copper Alloy 0.8µm minimum			
	-Durability	: 500 Mating cycles			
	-Delivered with Souriau contacts and Accessories				
	-Temperature Range	65°C to +200°C			
	-Salt Spray	: 500 hours			

: 41.72 g ± 10%

8D 0

G

13

S

04

В

F

А

Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	23.01		
R2	20.62		
S	28.6±0.3		
V	20.83+0/-1.25		
W	2.1/2.5		
Z	31.5 Max		
VV THREAD	M18x1-6g		


**ORIENTATION : A** 

CONTACT LAYOUT : 13-04

CONTACT TYPE : SOCKET(500 Matings)

Е

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recomment



	Φ		A		
	R				4
AS EXA	AMPLE				3
s which er of t indation untry FR	non-conformit ch does not co the Parties or to on, technical no Jurisd	mply with by a third part			2
					-
		CUSTOME	R DRAWING	MOD N°	
Stee	el Recepta				
ar :			PROJECT <b>59</b>		1
J.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
	DRG N° 4BA-C			SHEET	
50	B B		A		J

ſ	т	۵	н <b>т</b>	m	D	0	
		Contact Layout				Pa	anel Cutout
4		$\begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ &$			Â.	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING	
		Contacts (Insert arrangement 13-4)   Location   Contact position ID X-axis (mm) Y-axis (mm)   A + 0.00 (0.00) + 150 (3.81)   B + 146 (3.71) + 0.35 (0.89)   C + 0.00 (0.00) - 0.83 (2.11)   D - 146 (3.71) + 0.35 (0.89)   ent Number of contacts Size contacts Service rating Contact location   4 16 I All MS20051-4					2 21_
ى ى						Dim ØA ØAA R1 ØT	
	L						
						SOURIAU shall not be lial due to a use of the Pro the Specifications issued b (professional reco	roducts whi by either of
N						PN: 81	Country FR D013S
					A 15-10-201 ISS DATE Designed By:	.6 First Release Latest modification - by Date:	
					TITLE	Stain	less Ste
<b>_</b>					SCALE NA		ral linear erances: ±
					SOURIAL	J WWW.SOUF	RIAU.CO
					FORMAT A3		JRIAU 01350
	Н	G	F	E	D	С	

