Data sheet | Item number: 890-527

Shield connecting plate; 5-pole; for plugs

www.wago.com/890-527



Item description

Shield termination WINSTA® MINI 5-pole

Put your trust in tried-and-tested accuracy for the electrical installation in your project: The shield termination from the WINSTA® MINI product line. An extensive range of accessories rounds out the WINSTA® product line from WAGO. Particularly where space is tight, our smallest pluggable connection system, WINSTA® MINI, conveniently displays its advantageous properties. It saves space, and, thanks to Push-in CAGE CLAMP® spring

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222. www.wago.com/890-527



pressure connection technology, it also saves time, since the installation is low-maintenance and requires no screw connections.

WINSTA® MINI solutions for your electrical installation - protected against mismating and maintenance-free

The WINSTA® Pluggable Connection System is perfectly tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently faster, more reliable, and error-free. Use of this pre-assembled system decreases assembly times and installation errors at the construction site. Now you can also reduce installation costs without compromising quality and safety: The WINSTA® MINI accessory with protection against mismating reduces the need for servicing and prevents unnecessary downtime.

- easy tool-free operation, a wide range of coding options
- quick replacement of defective units during ongoing operation

Data

Connection data

Connection 1

Pole number 5	
---------------	--

Mechanical Data

Suitable	for plugs
Suitable	for plugs

Material Data

Note (material data)

Information on material specifications can be found here

Weight	1.8 g
Material	Copper (SE Cu); special tin coating

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

eCl@ss 10.0 27-44-06-92

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Do you have any questions about our products?

Hansastr. 27

We are always happy to take your call at +49 (571) 887-44222.

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

06.09.2023 Page 2/3

Data sheet | Item number: 890-527

www.wago.com/890-527



Customs tariff number	85366990990	
GTIN	4055143672764	
Country of origin	DE	
Packaging type	box	
PU (SPU)	50 (1) pcs	
ETIM 7.0	EC002863	
ETIM 8.0	EC002863	
eCl@ss 9.0	27-44-06-92	

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Documentation

Bid Text

890-527 X81 - Datei	2019 年2月19日	xml 2.6 kB	Download
890-527 doc - Datei	2018 年3月21日	doc 23.0 kB	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-527 URL Download Shield connecting plate; 5-pole; for plugs

Installation Notes

Product family

WINSTA® MINI

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.