NOTES:	31-5329-72RFX	REVISIONS	
I. MATERIALS OF CONSTRUCTION: BODY = BRASS (ASTM-BI6 HO2, C36000), NICKEL PLATED (.00100 MIN) THICK CONTACT = PHOSPHOR BRONZE, GOLD PLATED (.000003 MIN) THICK LOCK RING = BRASS (QQ-B-613), NICKEL PLATED (.00100 MIN) THICK INSULATORS (2) = PBT POLYESTER	THIRD ANGLE PROJ. B	DESCRIPTION RELEASE TO MFG. SEE SHEET I	DATE ECO APPR 8/1/05 45657 CPM
2. PACKAGE IN BAG, MARK BAG: "31-5329-72RFX YYWW"			
3> BNC LUG ORIENTATION RELATIVE TO PCB LEGS.			
.075 [I,91] 4 LEGS Ø.235 [5,97] Ø.433 [II]	.831 ±.008 [21,11 ±0,2]	INTERFACE PE MIL-STD-348 BNC SERIES FIGURES 301	8
Ø .037 [0,94]			
RECOMMENDED PCB MOUNTING HOLE DIM'S SCALE 3.000		CUSTOMER OUTLING	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° NOTICE - These drawings, specifications, or other data (1) are, and remain the	DRAWN DATE C. McGRATH 7/20/05 ENGINEER DATE	75 OHM BNC PCB MOUNT RECEPTACLE	Amphenol RF Danbury, CT, USA Tainan, Taiwan
property of Amphenol Čorp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, aranting	O. BARTHELMES 7/20/05 APPROVED DATE		www.amphenolrf.com SCALE: 6.0:1 SHEET 2 OF 2
rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	CAD FILE I:\BNC_75\3I-5329-72RFX	code id dwg sizedrawing no. 74868 B 31	-5329-72RFX B