



CORE DIMENSIONS **28T0500-100**

UNCOATED CORE

	MM	INCHES		MM	INCHES
OD	12.70	(.500)	±	.25	(.010)
ID	7.92	(.312)	±	.25	(.010)
TH	6.35	(.250)	±	.18	(.007)

EPOXY COATING **28T0500-10H**

OD	12.85	(.506)	±	.41	(.016)
ID	7.77	(.306)	±	.41	(.016)
TH	6.50	(.256)	±	.33	(.013)

WEIGHT / K 2.3965 KGS 5.2833 LBS

INITIAL PERMEABILITY **850**

ROOM TEMPERATURE ELECTRICAL SPECIFICATION

	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L1-1T	-20.0%	0.41	0.510	0.61	20.0%	100	6.61	10	1

COATING SPECIFICATIONS

TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Black Epoxy	(0.1524 / 6.0)	1000	1.20

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft	2009/9/22	Jcai
B	Update Logo, NOTES, coating colour, Q value	2020/4/12	WS

Date: 2009/9/22	Toling:T0500	Rev: A
Drawn By: Jcai	Title # 28T0500-10H	

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.