

**Ratings**

Voltage: 150 V  
 Temperature: -40~70 °C

**Conductor**

Conductor count: 8  
 Gauge: 32 AWG 0.04 mm<sup>2</sup>  
 Material: Tinned copper strands  
 Strand size:  $\varnothing 0.05 \times 19$   
 Resistance at 20 °C: 590  $\Omega$ /km Max

**Insulator**

Material: HDPE  
 Color: black, white, red, yellow, blue, green, orange, purple  
 Diameter:  $\varnothing 0.55 \pm 0.10$  mm  
 Nominal thickness: 0.15 mm  
 Resistance at 20 °C: 100 M $\Omega$  /km Min

**Wrap**

Material: cotton paper

**Filler**



Material: aramid fiber

**Outer jacket**

Material: TPU  
 Color: gray  
 Diameter:  $\varnothing 3 \pm 0.20$  mm  
 Nominal thickness: 0.50 mm

**Tests**

Tensile strength: 15 kgf min  
 Dielectric test: 1500 V dc for 1 minute without breakdown  
 Bend test at 200 g,  $\pm 60^\circ$ , 30 cycles /min: 15,000 cycle minimum



Revision:	Date:	Description:	Prepared: PB <small>Digitally signed by PB Date: 2022.09.20 11:05:11 -07'00'</small>	Notes:  RoHS compliant Jacket meets ISO 10993 Biological Compatibility Phthalate and halogen free Function test: no open, no short, no intermittent	<h1>TENSILITY</h1> <small>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</small>
A	9/9/2022	Initial release	Verified: MP <small>Digitally signed by MP Date: 2022.09.21 10:40:00 -07'00'</small>		
			Dimensions are in millimeters. Tolerances: X: $\pm 0.5$ mm X.X: $\pm 0.3$ mm X.XX: $\pm 0.05$ mm	Description: Wire, 8C TS, 32 AWG, 150V, 70C, 3.0 mm, TPU, 75A, gray, WBL	Size: A Part number: 30-02757
					Scale: 20:1  Sheet 1 of 1

5

4

3

2

1